



**NAGAR NIGAM BHILAI**

**NIT**

वार्ड क्र-19 शास्त्री नगर कैम्प 01 यादव समाज सामुदायिक भवन विस्तारीकरण कार्य।

AS PER PWD BUILDING S.O.R 01.01.2015

| S.NO | PARTICULAR  | QTY  | UNIT |
|------|---|--|------|
| 1    | Grading roof for water proofing treatment with:<br>Cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size)   | 5.63   | cum  |
| 2    | Removing mortars from stones and concrete articles and cleaning the same. (Stacks of cleaned material shall be measured).<br>In cement mortar   | 5.63   | cum  |
| 3    | 6 mm thick cement plaster of mix: In Cement Mortar 1:4 (1 cement : 4 fine sand)   | 63.37  | sqm  |
| 4    | 12mm thick cement plaster of mix: In Cement Mortar 1:6 (1 cement : 6 fine sand)   | 294.90   | sqm  |
| 5    | 15mm thick cement plaster of mix: In Cement Mortar 1:6 (1 cement : 6 fine sand)   | 423.01   | sqm  |
| 6    | Providing and fixing steel door with M.S. sheet 1mm thick, frame of angle iron, diagonal braces of angle/ flat iron of suitable size, 3.00 mm M.S. gusset plates at junctions and corners, all necessary fittings complete including applying a priming coat of red oxide zinc chromate primer..  | 561.60   | kg   |
| 7    | Providing and fixing M.S. grill of approved pattern made of M.S. flats or square or round bars welded to steel frame of windows etc. including applying a priming coat of red oxide zinc chromate primer..  | 270.00   | kg   |
| 8    | Providing and laying vitrified floor tiles with soluble salt printing, of size 600x600mm with water absorption less than 0.5% and conforming to IS: 15622 of approved make, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand) including grouting the joints with white cement and matching pigments etc. complete.        | 111.92   | sqm  |
| 9    | Distempering with acrylic washable distemper to give an even shade: on new work.(two or more coats)   | 781.28   | sqm  |
| 10   | Painting new exterior surface (two or more coats) with PREMIUM TEXTURED paint as per manufacturer's specifications to give protective and decorative finish including cleaning washing of surface etc. complete with:<br>On new work (Two or more coats )   | 423.01   | sqm  |
| 11   | Painting on new work (two or more coats) to give an even shade with.Premium synthetic enamel paint (2nd top most approved branded quality) to give an even shade .  | 60.12  | sqm  |
| 12   | Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with matching pigment complete. |  |      |
|      | Size upto 200x300mm   | 107.10   | sqm  |
|      |    |  |      |
|      | <b>ASST. ENGINEER</b>   |  |      |
|      | Nagar Palik Nigam, Bhilai   | Nagar Palik Nigam, Bhilai  |      |