



**MUNICIPAL CORPORATION BHILAI (C.G.)****NIT****वार्ड क्र.-27 राजीव सियान उद्यान का सौंदर्यीकरण कार्य।****As per Bulding SOR 1.01.2015/ Non Sor**

S.NO	PARTICULAR	Q	U
1	Surface dressing of the ground including removing vegetation and making up undulations and in-equalities not exceeding 15 cms in depth/ height including disposal of rubbish upto 1.5 m lift and lead upto 50m (at least 5m away from the dressed area). sqm 7.20		
		<b>3600.00</b>	<b>cum</b>
2	Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in:		
	Cement Mortar 1:6 (1 cement : 6 coarse sand) cum 3263.00		
		<b>9.60</b>	<b>cum</b>
3	Providing and laying nominal mix reinforced cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work.		
	1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).		
		<b>9.60</b>	<b>cum</b>
4	Providing and filling in plinth with sand/ Crusher dust and hard moorum under floor in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering, including dressing etc. complete.		
	footing	<b>40.00</b>	<b>cum</b>
5	Supplying and stacking of good earth at site including royalty, loading, unloading and carriage upto 5 km (earth measured in stacks will be reduced by 20% for payment). cum 201.00		
		<b>96.00</b>	<b>cum</b>
6	Spreading of sludge, dump manure or/and good earth in required. thickness (Cost of sludge, dump manure or/ and good earth to be paid separately). cum	<b>96.00</b>	<b>cum</b>
7	Providing & laying 60mm thick precast interlocking concrete blocks of approved size (approx 305 sqcm) and shape/ pattern, over 40 mm thick average complete coarse sand bed with joints of 3mm thick filled by fine sand including leveling with surface vibrator, temping and sweeping etc. complete of minimum compressive strength of 250. kg/sq.cm		
	12.65.2 Pigment Coloured (rubber mould) precast interlock concrete blocks sqm	<b>450.00</b>	<b>cum</b>
8	Painting on new work (two or more coats) to give an even shade with:		
	Premium synthetic enamel paint	<b>360.00</b>	<b>sqm</b>
9	Painting exterior surface with ACRYLIC SMOOTH exterior paint of. required shade as per manufacturer's specifications to give protective and decorative finish including cleaning washing of surface etc. complete with:		
	On old work (One or more coats applied @ 0.83 ltr/ 10 sqm) sqm	<b>120.00</b>	<b>sqm</b>
	<b>NON-SOR</b>		
1	Garden Chair	<b>2.00</b>	<b>no.</b>
			
			
	<b>ASSTT.ENGINEER</b>		<b>SUB ENGINEER</b>
	<b>Nagar Palik Nigam, Bhilai</b>		<b>Nagar Palik Nigam, Bhilai</b>