MUNICIPAL CORPORATION BHILAI (C.G.)

NIT

S.No.	rk :- वार्ड क्र. 51 सेक्टर 04 में 03 नग बोर संधारण कार्य। Description and details of work	Qty.	unit
1a	Boring/drilling bore well perfectly vertical for the specified depth suitable to receive required dia for casing/ strainer pipe, by suitable method prescribed in IS: 2800 (part I), including collecting samples from different strata, preparing and submitting strata chart/bore log, including hire & running charges of all equipments, tools, plants & machineries required for the job, all complete as per direction of Engineer–in-charge upto 90 metre depth below ground level. 150 mm dia.	99	Rmt
1b	Boring/drilling bore well perfectly vertical for the specified depth suitable to receive required dia for casing/ strainer pipe, by suitable methodprescribedRocky strata including Boulders. 150 mm dia.	84	Rmt
2	Providing ISI Mark 32 mm dia G.I. (B class) riser pipe and M.S. plunger rod in 3 meter length socketed on one end as per IS: 1239 (Part I) 1990 with up to date amendments and socket as per IS: 2062/1990 up to date amendments.	75	Rmt
3	Providing and placing in position India Mark II hand pump with 32 mm diameter riser pipe assembly complete with all accessories (riser pipe and plunger rod to be paid separately).	3	each
4	Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work.1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 40mm nominal size).	3	cum
5	Neat Cement punning.	15	sqm
6	Supplying, assembling, lowering and fixing in vertical position in bore well, ISI marked G.I. casing pipe (Plain) medium class in 4 to 7 meters length one end fitted with socket as per IS: 1239 (Part-1&Part-2) 1992 with IVth revision (Up-to-date amendments), of reputed & approved make, including required hire & labour charges, fittings & accessories, all complete, for all depths, as per direction of Engineer- in-charge. 150 mm nominal dia	(DS·, 'O	Rmt
7	Supplying, installation, testing and commissioning of submersible pump set for water supply system with submersible motor directly coupled to multistage submersible1hp single phase	1	each
8	Supplying and laying following sizes additional one number, FRLS PVC insulated /XLPE, PVC sheathed, steel armoured, aluminium conductor power cable of 1.1 KV grade direct in ground as in the same trench in one tier horizontal formation at a depth not less than 40 cm and upto 90 cm including excavtion, sand cushioning, protective covering and refilling the trench etc as per specification, IS: 1554 (1988, Part 1) / IS: 7098 (1988, Part 1). 2 x 4 sq. mm	95	Metre

100		Sign and the second
	Supply, installation, testing and commissioning of 1-3 HP 1 phase submersible motor starter cum control wall/ floor mounted type made out of not less than 1.6 mm thick MS sheet and comprising of following panel	
	mounting switchgears there in including connection inter-connection etc.	
9	as required.	1 each
	a) Phase indicating lamps with fuses and toggle switches 1 set	
	b) 1/2/3 HP 1 phase DOL starter with over load and no volt relay 1 No	· All
	c) 25 A "C" curve DPMCB 1 No	The state of the s
	d) Voltmeter 0-250 V 1 set	
	a) Ammotor 0 10 A 1 cot	

EXECUTIVE ENGINEER
MUNICIPAL CORPORATION
BHILAI

ASSISTANT ENGINEER
MUNICIPAL CORPORATION
BHILAI

SUB ENGINEER
MUNICIPAL CORPORATION
BHILAI