MUNICIPAL CORPORATION OF BHILAI

NIT

कार्य का नाम:— वार्ड क्रमांक 25 शर्मा कॉलोनी में सामुदायिक भवन का संघारण कार्य।

As Per PWD Building SOR 01.01.2015 Electrical SOR 1.06.2020,

N.	PARTICULERS OF ITEMS	Quantity	UOM
1	Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work.1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size).	0.45	Cum
7	Providing and making 6mm thick cement plaster of mix: In Cement mortar 1:3 (1 cement: 3 fine sand)	80.00	Sqm
3	Providing and making 12mm thick cement plaster of mix: In Cement mortar 1:4 (1 cement : 4 fine sand)	47.25	Sqm
4	Providing and making 15mm thick cement plaster of mix: In Cement mortar 1:5 (1 cement : 5 fine sand)	64.00	Sqm
5	Providing and fixing steel door/ window with M.S. sheet 1mm thick, frame of angle iron, diagonal braces of angle/ flat iron of suitable size, 3.00 mm M.S. gusset plates at junctions and corners, all necessary fittings complete including applying a priming coat of red oxide zinc chromate primer.	132.00	KG
6	Providing and laying vitrified floor tiles with soluble salt printing, of size $600x600mm$ with water absorption less than 0.5% and conforming to IS: 15622 of approved make, laid on 20mm thick cement mortar 1:4 (1 cement: 4 coarse sand) including grouting the joints with white cement and matching pigments etc.	33.00	Sqm
7	Providing and fixing ceramic glazed wall tiles conforming to IS: 13622 of approved make, colours, shades and size on wall and dados over 12 mm thick become of cement Mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with matching	1	0 Sqn
8	Distempering with acrylic washable distemper to give an even shade. On new	47.2	5 Sqi
9	Providing and applying plaster of paris putty over plastered wall surface including scaffolding complete More than 2 mm thickness to make surface even and smooth the and line and level.		00 Sq
1	Painting exterior surface with PREMIUM ACRYLIC SMOOTH exterior paint of required shade as per manufacturer's specifications to give protective and decorative finish including cleaning washing of surface etc. complete with: On new work (Two or more coats applied @ 1.43 ltr/ 10 sqm over and including in the part of exterior primer applied @ 2.20 kg/ 10 sqm)	64.	
-	1 (One or more coats applied (a) 0.83 iii 10 squi)	70.	.00 So
H	Distempering with acrylic washable distemper to give an even shader of the	127	7.25 Se
-	work (Two or more coats) Painting on new work (two or more coats) to give an even shade with: Satin synthetic enamel paint	7.	14 S

S.N.	PARTICULERS OF ITEMS	Quantity	UOM	
14	Painting on old work (one or more coats) to give an even shade with:Satin	4.00	Ç ım	
	Synthetic enamel paint Electrical SOr Lum-Sum As Per PWD Electrical SOR 1-06-2020 Service 17th	k -	- 1	

कार्यपाली अभियन्ता नगर पालिक निगम, भिलाई

सहायक अभियन्ता नगर पालिक निगम, भिलाई

चप अभियन्ता नगर पालिक निगम, भिलाई