MUNICIPAL CORPORATION OF BHILAI

NIT

वार्ड क्र. 41 औद्योगिक क्षेत्र छावनी में लक्ष्मण नगर तालाब के समीप पंप हाउस एवं चबूतरा संधारण कार्य।

(As Per PWD Building SOR 01.01.2015)

SN	PARTICULERS OF ITEMS	QTY.	UNIT
1	Demolishing R.C.C. work including stacking of steel bars and disposal of unserviceable material within	1.23	Cum
	50 metre lead. Demolishing cement concrete including disposal of material within 50 metre lead.	0.72	Cum
	1:3:6 or richer mix Demolishing brick masonry including arches, stacking of serviceable material disposal of unserviceable material within 50 metres lead.	0.56	Cum
4	In cement mortar. Excavation for all types and sizes of foundations, trenches and drains or for any other purpose including disposal of excavated stuff upto 1.5 m lift and lead upto 50m (at least 5m away from the excavated area),	2.88	Cum
5	including dressing and leveling of pits. In all types of soils. Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work.1:4:8 (1 cement : 4 coarse sand : 8	1.38	Cum
6	Providing and laying nominal mix reinforcement cement concrete with crushed stone aggregate using concrete mixer in all works upto floor five level excluding cost of reinforcement and form work. 1:1 ½:3 (1 cement: 1 ½ coarse sand: 3 graded stone aggregate 20mm nominal size)	3.60	Cum
7	Providing and laying nominal mix reinforcement cement concrete with crushed stone aggregate using concrete mixer in all works upto floor five level excluding cost of reinforcement and form work. 1:1 ½:3 (1 cement: 1 ½ coarse sand: 3 graded stone aggregate 20mm nominal size) + Extra for laying PCC/RCC of any grade in superstructure above plinth level for every floor or part	1.23	Cum
8	thereof in addition to rate for foundation and plinth: Providing and placing in position reinforcement for R.C.C. work including straightening, cutting, bending, binding etc. complete as per drawings including cost of binding wire in foundation and plinth all complete:Thermo-Mechanically treated bars.	482.50	Kg
•	Providing and fixing form work including centring, shuttering, strutting, staging, propping bracing etc.		
A	Foundations, footings, bases of columns plinth beam, curtain wall in any shape and size and all type of wall below plinth level.	14.40	Sqm
В	Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ)	26.65	Sqn
	Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in: Cement Mortar 1:6 (1 cement : 6 coarse sand)	1.73	Cun
	Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in: Cement Mortar 1:6 (1 cement : 6 coarse sand) + Extra for brick work in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth:	0.84	Cun
12	Providing and filling in plinth with sand/ Crusher dust and hard moorum under floor in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering, including dressing etc. complete.	23.84	Cun
13	Providing and making 6mm thick cement plaster of mix: In Cement mortar 1:3 (1 cement : 3 fine sand)	12.25	Sqn
14	Providing and making 12mm thick cement plaster of mix: In Cement Mortar 1:5 (1 cement : 5 fine sand)	59.28	Sqm
15	Providing and making 15mm thick cement plaster on the rough side of single or half brick wall of mix: In Cement Mortar 1:5 (1 cement: 5 fine sand)	43.20	Sqm

Si	PARTICULERS OF ITEMS	QTY.	UNIT
16	Providing and fixing M.S. grill of approved pattern made of M.S. flats or square or round bars welded to	106.50	Kg
17	Providing and fixing steel door/ window with M.S. sheet 1mm thick, frame of angle iron, diagonal braces of angle/ flat iron of suitable size, 3.00 mm M.S. gusset plates at junctions and corners, all necessary fittings complete including applying a priming coat of red oxide zinc chromate primer.	170.40	Kg
18	Providing and laying vitrified floor tiles with soluble salt printing, of size 600x600mm with water absorption less than 0.5% and conforming to 1S: 15622 of approved make, laid on 20mm thick cement mortar 1:4 (1 cement: 4 coarse sand) including grouting the joints with white cement and matching	16.64	Sqm
19	Providing & laying 60mm thick precast interlocking concrete blocks of approved size (approx 305 sqcm) and shape/ pattern, over 40 mm thick average complete coarse sand bed with joints of 3mm thick filled by fine sand including leveling with surface vibrator, temping andsweeping etc. complete of minimum compressive strength of 250 kg/sq.cm	100.00	Sqm
20	Pigment Coloured (rubber mould) precast interlock concrete blocks Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work. 1:1½:3 (1 cement: 1½ coarse sand: 3 graded stone aggregate 20mm nominal size).	3.15	Cum
21	Cement concrete flooring with cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20mm) finished with a floating coat of neat cement. 40 mm thick	24.50	Sqm
22	Distempering with acrylic washable distemper to give an even shade. On new work (Two or more coats)	_	·
	As Per Qty. of 6mm + 12 mm thick cement plaster	71.53	Sqm
	Painting exterior surface with PREMIUM ACRYLIC SMOOTH exterior paint of required shade as per manufacturer's specifications to give protective and decorative finish including cleaning washing of surface etc. complete with: On new work (Two or more coats applied @ 1.43 ltr/ 10 sqm over and including priming coat of exterior primer applied @ 2.20 kg/ 10 sqm)	- 20	
	As Per Qty. of 15 mm thick cement plaster	4.20	Sqm
24	Road SOR 01.01.2015 Cement Art Mural Work	20.00	Sqm

Executive Engineer
Municiapal Corporation
Bhilai

Assistant Engineer
Municipal Corporation
Bhilai

Sub Engineer

Municipal Corporation

Bhilai