MUNICIPAL CORPORATION BHILAI (C.G.)

NIT

work :- पेयजल हेतु बोर खनन कार्य 01 नग वार्ड कं.58 सेक्टर 04 सड़क 35 एवं 36 के समीप बोर खनन कार्य।

1	El		Building SOR 01.01.201
1		Qty.	Unit
	Description and details of work Boring drilling bore well perfectly vertical for the specified depth suitable to receive required dia for casing/ strainer pipe, by itable method prescribed in IS: 2800 (part 1), including collecting samples from different strata, preparing and submitting strata chart/bore log, including hire & running charges of all equipments, tools, plants & machineries required for the job, all complete as per direction of Engineer–in-charge upto 90 metre depth below ground level. All types of soil 150MM DIA	18	Rmt
1		90	Rmt
	Rocky strata including Boulder	80	
	150MM DIA Supplying, assembling, lowering and fixing in vertical position in bore well, ISI marked G.I. casing pipe (Plain) medium class in 4 to 7 meters length one end fitted with socket as per IS: 1239 (Part-1&Part-2) 1992 with IVth medium class in 4 to 7 meters length one end fitted with socket as per IS: 1239 (Part-1&Part-2) 1992 with IVth medium class in 4 to 7 meters length one end fitted with socket as per IS: 1239 (Part-1&Part-2) 1992 with IVth medium class in 4 to 7 meters length one end fitted with socket as per IS: 1239 (Part-1&Part-2) 1992 with IVth medium class in 4 to 7 meters length one end fitted with socket as per IS: 1239 (Part-1&Part-2) 1992 with IVth medium class in 4 to 7 meters length one end fitted with socket as per IS: 1239 (Part-1&Part-2) 1992 with IVth medium class in 4 to 7 meters length one end fitted with socket as per IS: 1239 (Part-1&Part-2) 1992 with IVth medium class in 4 to 7 meters length one end fitted with socket as per IS: 1239 (Part-1&Part-2) 1992 with IVth medium class in 4 to 7 meters length one end fitted with socket as per IS: 1239 (Part-1&Part-2) 1992 with IVth medium class in 4 to 7 meters length one end fitted with socket as per IS: 1239 (Part-1&Part-2) 1992 with IVth medium class in 4 to 7 meters length one end fitted with socket as per IS: 1239 (Part-1&Part-2) 1992 with IVth medium class in 4 to 7 meters length one end fitted with socket as per IS: 1239 (Part-1&Part-2) 1992 with IVth medium class in 4 to 7 meters length one end fitted with socket as per IS: 1239 (Part-1&Part-2) 1992 with IVth medium class in 4 to 7 meters length one end fitted with socket as per IS: 1239 (Part-1&Part-2) 1992 with IVth medium class in 4 to 7 meters length one end fitted with socket as per IS: 1239 (Part-1&Part-2) 1992 with IVth medium class in 4 to 7 meters length one end fitted with socket as per IS: 1239 (Part-1&Part-2) 1992 with IVth medium class in 4 to 7 meters length one end fitted with socket as per IS: 1239 (Part-1&Part-2) 1992 with IVth medium class in 4 to 7 meters lengt	19.00	Rmt
1	& accessories, all complete, for all depths, as per direction of Engineer- in-charge. 150mm nominal size dia Development of tube well in accordance with IS: 2800 (part I) and IS: 11189, to establish maximum rate of usable water yield without sand content (beyond permissible limit), with required capacity air compressor, running the water yield without sand content (beyond permissible limit), with required capacity air compressor, running the compressor for required time till well is fully. Providing and fixing suitable size threaded mild steel cap or spot welded plate to the top of bore well housing/ casing pipe, removable as per requirement, all complete for bore well welded plate to the top of bore well housing/ casing pipe.	1.00	each
5	of 150mm nominal size dia. Providing 181 Mark 32 mm dia G.1 (B class) riser pipe and M. plunger rod in 3 meter length socketed on one end as per 18: 1239 (Part I) 1990 with up to date amendments and socket as per 18: 2062/1990 up to date	21.00	* Rmt
	Excavation for all types and sizes of foundations, trenches and drains or for any other purpose including disposal of excavated stuff upto 1.5 m lift and lead upto 50m (at least 5m away from the excavated area), disposal of excavated stuff upto 1.5 m lift and lead upto 50m (Below GB).	5	cum
6	disposal of excavated stuff upto 1.3 in fit and redd upto 1.3 in fit an	0.32	cum
7	in all works upto pinth level excluding cost of form work. excluding cost of form work flooring with cement concrete 1:2-4 (1 cement : 2 coarse sand : 4 graded stone	4.00	sqm
8		1.00	Each
	Supply, installation, testing and commissioning of 1-3 HP 1 phase submersible motor starter cum control. Supply, installation, testing and commissioning of 1-3 HP 1 phase submersible motor starter cum control. wall/ floor mounted type made out of not less than 1.6 mm thick MS sheet and comprising of following wall/ floor mounting switchgears there in including connection inter-connection etc. as required. a) Phase indicating lamps with fuses and toggle switches 1 set b) 1/2/3 HP 1 phase DOL starter with over load and no volt relay 1 No c) 25 A "C" curve DPMCB 1 No d) Voltmeter 0-250 V 1 set	1.00	Each
-	e) Ammeter 0-10 A 1 set Supplying and laying following sizes one number PVC insulated/ XLPE, PVC sheathed, steel armoured, sluminium conductor power cable of 1.1 KV grade direct in ground including excavation, sand cushioning, aluminium conductor power cable of 1.2 KV grade direct in ground including excavation, sand cushioning, aluminium conductor power cable of 1.3 KV grade direct in ground including excavation, sand cushioning, aluminium conductor power cable of 1.3 KV grade direct in ground including excavation, sand cushioning, aluminium conductor power cable of 1.3 KV grade direct in ground including excavation, sand cushioning, aluminium conductor power cable of 1.1 KV grade direct in ground including excavation, sand cushioning, aluminium conductor power cable of 1.1 KV grade direct in ground including excavation, sand cushioning, aluminium conductor power cable of 1.1 KV grade direct in ground including excavation, sand cushioning, aluminium conductor power cable of 1.1 KV grade direct in ground including excavation.	30.00	Metre

MUNICIPAL CORPORATION BHILAI

MUNICIPAL CORPORATION BHILAI