## NAGAR NIGAM BHILAI

. 7- 3	NIT		
विधा	यक निधि अंतर्गत वार्ड क्र.—25 जवाहर नगर शिव मंदिर लोकांगन परिसर के पास सार्वजनिक डो	म शेड निम	णि कार्य
	(AS PER PWD BUILDING S.O.R 01.01.2015)		
NO.	PARTICULAR	QTY	UNIT
1	Excavation for all types and sizes of foundations, trenches and drains or for any other purpose including disposal of excavated stuff upto 1.5 m lift and lead upto 50m (at least 5m away from the excavated area), including dressing and leveling of pits.		
_	In all types of soils.	43.20	Cum
2	Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work. 1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size).		
3	Providing and Lucian in the control of the control	2.88	Cum
	Providing and laying nominal mix einforcement cement concrete with crushed stone aggregate using concrete mixer in all works upto floor five level excluding cost of reinforcement and form work.1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).		
4	Providing and placing in position with Company	11.94	Cum
	Providing and placing in position reinforcement for R.C.C. work including straightening, cutting, bending, binding etc. complete as per drawings including cost of binding wire all complete:  Thermo-Mechanically treated bars FE 415		
5	Structural ctool work wines deal to be a	1193.75	Kg
	Structural steel work riveted or bolted or welded in built-up sections, trusses and frames work upto a height of 5m above plinth level, including cutting, hoisting, fixing in position and applying a priming coat of red oxide zinc chromate primer.	•	
6	Supply and fiving of war at 1	8132.14	Kg
J	Supply and fixing of precoated galvanized iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-charge) 0.50 mm +/- 5% total coated thickness (TCT), Zinc coating 120gsm as per IS: 277 in 240mpa steel grade, of purlins, rafters and trusses and including cutting to size and shape wherever required.		~~5
7	Providing and making 15mm thick cement plactor on the second second	100.44	Sqm
-	Providing and making 15mm thick cement plaster on the rough side of single or half brick wall of mix: In Cement Mortar 1:6 (1 cement : 6 fine sand)		
8	Painting on new work (two or more coats) to give an even shade with:	12.80	Sqm
	Aluminium paint	-	•
(BD) \ \\ \forall 1 \.		94.61	Sqm
	ASSTT.ENGINEER SUB ENGINEER		
Nagar Palik Nigam, Bhilai Nagar Palik Nigam, Bhilai			

Nagar Palik Nigam, Bhilai