

NAGAR NIGAM BHILAI

NIT

विधायक निधि अंतर्गत वार्ड क्र.—14 शांतिनगर स्वर्णकार पारा में सामुदायिक भवन निर्माण कार्य।

S.NO		QTY	UNIT
1	6 mm thick cement plaster of mix: In Cement Mortar 1:4 (1 cement : 4 fine sand)		
		99.06	sqm
2	12mm thick cement plaster of mix: In Cement Mortar 1:6 (1 cement : 6 fine sand)		
	- The state of the	219.90	sqm
3	15mm thick cement plaster of mix: In Cement Mortar 1:6 (1 cement : 6 fine sand)		- 1
	Committee of the content worth 1.0 (1 centent . 0 the saild)	242.88	sqm
4	Distempering with comilia weekahle distance at a in a set of the s	242.00	- Sqiii
	Distempering with acrylic washable distemper to give an even shade: on new work.(two or more coats)		
	qty of 6mm+12mm	318.96	sqm
5	Painting new exterior surface (two or more coats) with PREMIUM TEXTURED paint as decorative finish	310.70	Jqiii
	including cleaning washing of surface etc. complete with: On old work (One or more coats applied @ 0.83 ltr/		
	10 sqm)		
	qty of 15mm	242.88	sqm
6	25mm thick cement concrete flooring with 1:2:4 cement concrete (1 cement : 2 coarse sand : 4 graded stone		
	aggregate 12.5 mm nominal size) finished with floating cost of neat cement.	*	
		8.75	sqm
7	Providing and applying plaster of paris putty over plastered wall surface including scaffolding complete Upto		
	2 mm thickness to make surface even and smooth in line and level.		-
		318.96	sqm
8	Providing and fixing M.S. grill of approved pattern made of M.S. flats or square or round bars welded to		
	frame with all necessary fitting complete including applying a priming of red oxide zinc chromate primer.	,	
		400.00	kg
9	Providing and fixing steel door/ window with M.S. sheet 1mm thick, frame of angle iron, diagonal braces of		
	angle/ flat iron of suitable size, 3.00 mm M.S. gusset plates at junctions and corners, all necessary fittings		
	complete including applying a priming coat of red oxide zinc chromate primer.		
		200.00	kg
10	Providing and laying vitrified floor tiles with soluble salt printing, of size 600x600mmIS: 15622 of		
	approved make, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand) including grouting the joints		
	with white cement and matching pigments etc. complete.		
		120.32	sqm
- 1	Providing and fixing in position collapsible steel shutters with vertical channels 20x10x2mm and braced with		
	flat iron diagonals 20x5mm size arrangement stoppers, handles including applying a priming coat of red		
	oxide zinc chromate primer.		
_		5.00	sqm
1	Chequerred precast cement concrete tiles 22mm thick in footpath & courtyard jointed with neat cement slurry		
	mixed with pigment to match the shade of tile including cleaning of joint etc complete on 20 mm thick bed of		
	ement mortar 1:4 (1 cement :4 coarse sand): Light shade using white cement		
		13.20	

P

ASSTT.ENGINEER

SUBENCINEER

Nagar Palik Nigam, Bhilai

Nagar Palik Nigam, Bhilai

