NAGAR PALIK NIGAM BHILAI

NIT

वार्ड क्र.—16 कुरूद (नया वार्ड—21 कैलाश नगर) प्रगतिनगर शासकीय प्राथमिक शाला (22100726211) का संधारण कार्य।

S.NO	AS PER PWD BUILDING S.O.R 01.01.2015 & NON SOR ITEM PARTICULAR	QTY	UNIT
1	Providing and laying vitrified floor tiles with soluble salt printing, of size 600x600mm with	V.,	OTTE
1	water absorption less than 0.5% and conforming to IS: 15622 of approved make, laid on		
	20mm thick cement mortar 1:4 (1 cement : 4 coarse sand) including grouting the joints with		
	white cement and matching pigments etc. complete.		
	D. The local state of the local	205.00	sqm
2	Providing and fixing ceramic glazed wall tiles conforming to IS: 15622 of approved make,		
	colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1		
	cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including		
	pointing in white cement mixed with matching pigment complete.		
	Size upto 200x300mm		
		49.20	sqm
3	Providing and laying rectified ceramic glazed floor tiles of size 300x300mm and above		
	conforming to IS: 15622 of approved make, colour, shade laid on 20 mm thick Cement Mortar		
	1:4 (1 cement : 4 coarse sand) including pointing the joints with white cement mixed with		
	matching pigment etc., complete.		
	Size 300x300mm		
	bathroom	67.00	sqm
4	Wall painting with acrylic premium emulsion (plastic) manufactured with the cow dung		
	processing emulsion paint of required shade to given an even shade. On old work (one or more		
	coats)		
		282.00	~~~
5	Painting exterior surface with SMOOTH exterior emulsion paint of manufacturerd with cow	202.00	sqm
	dung processing to give protective and decorative finish including cleaning washing of surface		
	etc. complete with: On old work (One or more coats applied @ 0.83 ltr/ 10 sqm)		
	work (one of more coats applied (20.65 III) 10 sqiii)		
		329.00	sqm
6	Providing and laying nominal mix plain cement concrete with crushed stone aggregate using	525.00	Sqiii
	concrete mixer in all works upto plinth level excluding cost of form work. 1:1½:3 (1 cement :		
	1½ coarse sand : 3 graded stone aggregate 20mm nominal size).		
	b sales aggs sgave zommi nommur sizo).		
		0.65	
7	25mm thick cement concrete flooring with 1:2:4 cement concrete (1 cement : 2 coarse sand : 4	0.05	sqm
	graded stone ggregate 12.5 mm nominal size) finished with floating cost of neat cement.		
	, was a starting cost of near content.		
		231.00	60-
8	Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of	201.00	sqm
	class designation 4.0 in foundation and plinth in: Cement Mortar 1:6 (1 cement : 6 coarse	a 8 a	
	sand)		
		6.00	sqm
9	Providing and making 15mm thick cement plaster on the rough side of single or half brick wall		Squi
	of mix: In Cement Mortar 1:6 (1 cement : 6 fine sand)		
10	D	99.00	sqm
10	Providing and making 12mm thick cement plaster of mix:		
, ,	In Cement Mortar 1:6 (1 cement : 6 fine sand) sqm		
		51.00	sqm

17	White Size 550x450 mm each Educational Wall Writing Work.	4.00	each
		1	
16	Providing and fixing vitreous china wash basin with C.I. brackets, 32 mm C.P. brass waste of standard pattern, including painting of brackets, cutting and making good the walls wherever required:		
16		3.00	each
15	Providing and fixing one piece construction white vitreous china squatting plate urinal with an integral rim longitudinal flushing pipe. Each		
1.5	Flat back type urinal of size 460x380x250mm	3.00	each
14	Providing and fixing white vitreous china urinal basin with waste fitting as per IS: 2556, and other couplings in C.P. brass complete:		
14	White Orissa pattern W.C. pan of size 580x440 mm each	3.00	each
13	Providing and fixing water closet squatting pan (Indian type W.C. pan), 100mm sand cast Iron P or S complete including cutting and making good the walls and floors wherever required:		
		37.26	sqm
	Painting on old work (one or more coats) to give an even shade with: Premium synthetic enamel paint		
12	@ 30kg/m2	1117.80	kg
11	Providing and fixing steel door/ window with M.S. sheet 1mm thick, frame of angle iron, diagonal braces of angle/ flat iron of suitable size, 3.00 mm M.S. gusset plates at junctions and corners, all necessary fittings complete includi g applying a priming coat of red oxide zinc chromate primer		

ASSTT.ENGINEER Nagar Palik Nigam, Bhilai

SUB ENGINEER
Nagar Palik Nigam, Bhilai