(3)

NAGAR PALIK NIGAM BHILAI

NIT

िं वायक निधि अंतर्गत वार्ड क्र.—29 वृंदानगर काली मंदिर वार्ड कार्यालय के पास सार्वजनिक भवन निर्माण कार्य | AS PER PWD BUILDING S.O.R 01.01.2015 & Elec. 01.06.2020

SN	PARTICULAR	QTY	UNIT
1	Excavation for all types and sizes of foundations, trenches and drains or forupto 50m (at least	inimate a productiva de la companya	
	5m away from the excavated area), including dressing and leveling of pits. In all types of soil		
-			
,	D. 'I'	24.78	cum
2	Providing and laying nominal mix cement concrete with crushed stone aggregate using concrete	Recognition of the second selection with	
	in roundation, plinth and at ground level excluding cost of form work		
-	1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size).		
3	Providing and laving naminal minutes	8.80	cum
	Providing and laying nominal mix reinforcement cement concrete with crushed stone aggregate		
	using concrete mixer in all works upto floor five level excluding cost of reinforcement and form		
	work.1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).		
		20.77	cum
4	Providing and placing in position reinforcement for R.C.C. work including straightening, cutting,		Cam
	bending, binding etc. complete as per drawings including cost of binding wire all complete:		
-	Thermo-Mechanically treated bars FE 415		
		10/0.00	
5	Providing and fixing formwork including centering, shuttering, strutting, staging, propping bracing	1868.90	kg
	etc. complete and including its removal at all levels, for:		
5.a	Foundations factions by C. I		
a	Foundations, footings, base of columns and plinth beam in any shape and size.		
5.b	Columns, Pillars, Piers and likes- rectangular or square in shape	30.80	sqm
	Testangular of square in snape	71.00	
5.c	Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ)	71.00	sqm
	(cast in situ)	-	
5.d	Beams, lintels, cantilevers & walls	130.58	sqm
	The state of the s		
6	Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of class	39.00	sqm
	designation 4.0 in foundation and plinth in: Cement Mortar 1:6 (1 Cement : 6 Coarse Sand)		
	The state of the s		
		4.92	cum
7	super structure Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894		
	2002 of class designation 4.0 in foundation and plinth in: Cement Mortar 1:6 (1 Cement : 6 Coarse Sand)	* .	
	Said)		
8	Providing and filling in plinth with sand/ Crusher dust and hard moorumdepth consolidating each	16.22	cum
	deposited layer by ramming and watering, including dressing etc. complete.		
	and watering, including dressing etc. complete.	2 - 12	
		31.80	(ilian)
1	Providing and laying damp proof course (upto 50mm thick) with plain cement concrete 1:2:4 (1	21.00	cum
	cement : 2 coarse sand : 4 graded crushed stone aggregate 20mm nominal size) including formwork		
		0.22	
0	Providing and fixing steel door with M.S. sheet 1mm thick, frame of angle iron, diagonal braces of	0.32	sqm
- 1	" an necessary fittings complete including applying a priming coat of red oxide gips above.		
	primer		

		127.20	kg
11	Providing and fixing M.S. grill of approved pattern made of M.S. flats or square or round bars welded to steel frame of windows etc. including applying a priming coat of red oxide zinc chromate primer.		
- 12		43.20	kg
12	6 mm thick cement plaster of mix: In Cement Mortar 1:4 (1 cement : 4 fine sand)		
	(* samu)	81.08	sam
13	12mm thick cement plaster of mix:	01.00	sqm
	In Cement Mortar 1:6 (1 cement : 6 fine sand)		
		85.20	sqm
14	15mm thick cement plaster of mix:		
	In Cement Mortar 1:6 (1 cement : 6 fine sand)		
		114.00	sqm
15	Providing and laying vitrified floor tiles with soluble salt printing, of size 600x600mm with water absorption less than 0.5% and onforming to IS: 15622 of approved make, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand) including grouting the joints with white cement and matching pigments etc. complete.		
		60.40	sqm
17	Distempering with washable distemper manufactured with the cow dung processing to give an even shade. On new work (one or more coats)		
	qty of no 12+13	166.28	sqm
18	Painting exterior surface with SMOOTH exterior emulsion paint of manufacturerd with cow dung processing to give protective and decorative finish including cleaning washing of surface etc. complete with: On new work (One or more coats applied @ 1.43 ltr/ 10 sqm)		- 7-1
_	qty of no 14	114.00	sqm
9	Painting on new work (two or more coats) to give an even shade with Premium synthetic enamel paint (2nd top most approved branded quality) to give an even shade.		34m
		21.36	sqm

ASSTT.ENGINEER Nagar Palik Nigam, Bhilai

SUB ENGINEER Nagar Palik Nigam, Bhilai