

MUNICIPAL CORPORATION OF BHILAI

वार्ड क्र. 48 जोन 03 खुर्सीपार स्थित केनाल रोड किनारे शिव मंदिर के पास डोम शेड, ग्रील लगाने का कार्य।

	(As Per PWD	(As Per PWD Building SOR			
S.N.	PARTICULERS OF ITEMS	Quantity	UOM		
1	Boring, providing and installing cast in situ single under reamed piles of specified diameter and length below pile cap in cement concrete 1:1½:3 (1 cement: 1½ coarse sand: 3 graded stone aggregate 20mm nominal size),required for boring true to vertical line etc. all complete. (Length of pile for payment shall be measured upto to the bottom of pile cap):	14.82	Metre		
2	Providing and laying nominal mix reinforced cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work. 1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).	2.72	Cum		
3	Structural steel work riveted or bolted or welded in built-up sections, trusses and frames work upto a height of 5m above plinth level, including cutting, hoisting, fixing in position and applying a priming coat of red oxide zinc chromate primer.	4578.71	Kg		
4	Providing and placing in position reinforcement for R.C.C. work including straightening, cutting, bending, binding etc. complete as per drawings including cost of binding wire all complete:Thermo-Mechanically treated bars	339.92	Kg		
5	Supply and fixing of precoated galvanized iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-charge) 0.50 mm +/- 5% total coated thickness (TCT), Zinc coating 120gsm as per IS: 277 in 240mpa steel grade, 5-7 upto any pitch in horizontal/ vertical or curved surfaces excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required.	121.03	Sqm		
6	Providing and fixing form work including centring, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for:				
(A)	Foundations, footings, bases of columns plinth beam, curtain wall in any shape and size and all type of wall below plinth level.	9.06	Sqm		
7	Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in: Cement Mortar 1:6 (1 cement : 6 coarse sand)	3.11	Cum		
8	Providing and making 12mm thick cement plaster of mix: In Cement mortar 1:4 (1 cement : 4 fine sand)	42.63	Sqm		
9	Painting exterior surface with PREMIUM ACRYLIC SMOOTH exterior paint of required shade as per manufacturer's specifications to give protective and decorative finish including cleaning washing of surface etc. complete with: On new work (Two or more coats applied @ 1.43 ltr/ 10 sqm over and including priming coat of exterior primer applied @ 2.20 kg/ 10 sqm)	20.85	Sqm		
10	Painting on new work (two or more coats) to give an even shade with: Aluminium paint	94.40	Sqm		
11	Providing and filling in plinth with sand/ Crusher dust and hard moorum under floor in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering, including dressing etc. complete.	14.82	Cum		
12	Providing & laying 60mm thick precast interlocking concrete blocks of approved size (approx 305 sqcm) and shape/ pattern, over 40 mm thick average complete coarse sand bed with joints of 3mm thick filled by fine sand including leveling with surface vibrator, temping and sweeping etc. complete of minimum compressive strength of 250 kg/sq.cm Plain/ normal coloured precast interlock concrete block	148.20	Sqm		
13	Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work. 1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size).	1.60	Cum		

S.I	N. PARTICULERS OF ITEMS	Quantity	でたし
14	Providing and fixing ceramic glazed wall tiles conforming to IS: 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement': 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with matching pigment complete. Size upto 200x300mm	2.96	Sqm
15	Providing and laying vitrified floor tiles with soluble salt printing, of size 600x600mm with water absorption less than 0.5% and conforming to IS: 15622 of approved make, laid on 20mm thick cement mortar 1:4 (1 cement: 4 coarse sand) including grouting the joints with white cement and matching pigments etc. complete.	5.93	Sqm
16	Excavation for all types and sizes of foundations, trenches and drains or for any other purpose including disposal of excavated stuff upto 1.5 m lift and lead upto 50m (at least 5m away from the excavated area), including dressing and leveling of pits. In all types of soils.	10.43	Cum
17	Columns, Pillars, Piers and likes- rectangular or square in shape	11.88	Sqm
18	Beams, lintels, cantilevers & walls Painting exterior surface with SMOOTH exterior and his surface with SMOOTH exterior and his surface with surfac	4.80	Sqm
	Painting exterior surface with SMOOTH exterior emulsion paint manufactured with th cow dung processing to give protective and decorative finish including cleaning washing of surface etc. complete with: On new work (two or more coats applied @ 1.43 ltr/ 10 sqm over)	90.00	Sqm
20	Painting on new work (two or more coats) to give an even shade with: Satin synthetic enamel paint	13.74	Sqm
۱۱ ۱۰	Providing and fixing M.S. grill of approved pattern made of M.S. flats or square or round bars welded to steel frame of windows etc. including applying a priming coat welded to frame with all ecessary fitting complete including applying a priming of red oxide zinc chromate primer.	96.00	Kg
ne	roviding and fixing steel door/ window with M.S. sheet 1mm thick, frame of angle iron, diagonal races of angle/ flat iron of suitable size, 3.00 mm M.S. gusset plates at junctions and corners, all eccessary fittings complete including applying a priming coat of red oxide zinc chromate primer.	160.00	Kg
sta	oviding stainless steel railing/ grill made of S.S. flats, hollow S.S. pipe or square/ rectangular ctions of approved design fixing in stair case, balcony or other places with metal fasteners and sinless steel bolts etc complete. Grade 304	80.00	Kg

Executive Engineer
Municiapal Corporation
Bhilai

Assistant Engineer
Municipal Corporation
Bhilai

Sub Engineer

Municipal Corporation

Bhilai