MUNICIPAL CORPORATION OF BHILAI

4

NIT

## कार्य का नाम :–वार्ड क्रमांक 33 संतोषी पारा विवेकानंद सार्वजनिक सुलभ शौचालय का संधारण कार्य।

## (As Per PWD Building SOR 01.01.2015 & Electric SOR 01.06.2020)

 $\langle \zeta \rangle$ 

S.N.	PARTICULERS OF ITEMS		
1	Providing, laying and jointing glazed stoneware pipes grade 'A' with stiff mixture of cement mortar in the proportion of 1:1 (1 cement : 1 fine sand) including testing of joints etc. complete : 100 mm diameter	Quantity 20	UOM m
2	Providing and constructing brick masonry road gully chamber 50x45x60cm with well burnt modular clay bricks crushing strength not less than 35kg/cm2 in cement mortar 1:4 (1 cement : 4 coarse sand) including 500 x 450 mm precast R.C.C. horizontal grating with frame complete as per standard design.	1	No.
3	Providing and laying cement concrete 1:5:10 (1 cement : 5 coarse sand : 10 graded stone aggregate 40 mm nominal size) all-round S.W. pipes including bed concrete 150mm thick as per standard design:100 mm diameter S.W. pipe	6	m
4	Providing and fixing on wall face or under floor UV stabilized Unplasticised Rigid PVC pipes (single socketed) having 3.2mm wall thickness conforming to IS : 13592 (4kg/sqcm) including required couplers, jointing with seal ring conforming to IS : 5382 leaving 10 mm gap for thermal expansion etc complete. 110 mm dia	10	М
5	Providing and fixing on wall face or under floor UV stabilized Unplasticised Rigid PVC pipes (single socketed) having 3.2mm wall thickness conforming to IS : 13592 (4kg/sqcm) including required couplers, jointing with seal ring conforming to IS : 5382 leaving 10 mm gap for thermal expansion etc complete. 150 mm dia	10.00	М
6	Demolishing brick masonry including arches, stacking of serviceable material disposal of unserviceable material within 50 metres lead. In cement mortar.	20.00	Cum
7	Providing and making 6mm thick cement plaster of mix: In Cement mortar 1:3 (1 cement : 3 fine sand)	45.00	Sqm
8	Providing and making 15mm thick cement plaster on the rough side of single or half brick wall of mix:In Cement Mortar 1:5 (1 cement : 5 fine sand)	45.00	Sqm
9	Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work.1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size).	3.60	Cum
10	Providing and constructing soak pit 1.20x1.20x1.20m filled with brickbats including S.W. drain pipe 100 mm diameter and 1.20 m long complete as per standard design.	1	Each
11	Providing and laying ceramic glazed floor tiles conforming to IS : 15622 of approved size, make, colour, shade laid on 20 mm thick Cement Mortar 1:4 (1 cement : 4 coarse sand) including pointing the joints with white cement mixed with matching pigment etc., complete. Size 300x300mm	18.00	Sqm
12	Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and 12 mm thick bed of cement Mortar 1:3cement slurry @ 3.3kg per sqm including pointing in white cement mixed with matching pigment complete. Size upto 200x300mm	32.00	Sqm

		Quantit	y UOM	
s.n.	PARTICULERS OF ITEMS Providing and fixing water closet squatting pan (Indian type W.C. pan ), 100mm sand cast Iron P or S trap, 10 litre low level P.V.C. flushing cistern (same colour) conforming to IS : 7231, with flush bend and other fittings and fixtures complete including cutting and making rood the walls and floors wherever required : WC pan of size 580x440 mm	2	Each	
13	7231, with flush bend and otherever required : good the walls and floors wherever required : good the walls and floors wherever required : where the second state of t	1	Cum	1
14	P.V.C. flushing cistern (same colour), containing of the	2	Eac	h
	standard partony	4	Eac	h
16	required : <u>White Size 550x450 mm</u> <u>Towel rail (600mm long x 20mm dia)</u> Providing and fixing flexible P.V.C. waste pipe for sink or wash basin including P.V.C. Providing and fixing flexible P.V.C. waste pipe for sink or wash basin including P.V.C.	2	Ead	:h
17	waste fittings complete.32 miles apacity P.V.C. low level flushing disterne	2	Ea	ch
18	7231, with all fittings and finance White	y e		
19	for hot & cold water supply includes. This includes jointing of pipes & fittings with one en- pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one en- CPVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete as per direction of Engineer in Charge.15 mm nominal outer dia Direct		.00	m
20	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, havingthermal stabil for hot & cold water supply including all CPVC plain &brass threaded fittings i/c fixing t pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one st CPVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete as per direction of Engineer in Charge.25 mm nominal outer d Pipes	ep   1	.5.00	m
21	Providing and laying in trenches G.I. pipes medium class complete with G.I. fittings including excavation of trenches, refilling the same and testing of joints complete:25 minominal bore	n dia.	20.00	Mt
22	Providing and laying in trenches G.I. pipes medium class complete with G.I. fittings including excavation of trenches, refilling the same and testing of joints complete 15 mm		20.00	Mt
23	nominal bore Providing and fixing on wall surface G.I. pipes medium class complete with G.I. fitting clamps, including cutting, making good the walls etc. and testing of joints complete: 25 dia meminal hore	s and mm	20.00	Mt
24	dia. nominal bore Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwe end): 25 mm nominal bore		1	No
25	Providing and fixing 15 mm nominal bore Brass bib/stop cock of approved quality: Bi (250 grams)	b cock	2	No
26	Distempering with acrylic washable distemper to give an even shade On old work (on more coats)Manufractured with the cow dung processing	e or	60.00	Sqn

\*\*

S.N.	PARTICULERS OF ITEMS	Quantity	UOM
27	Painting exterior surface with PREMIUM ACRYLIC SMOOTH exterior paint of required shade as per manufacturer's specifications to give protective and decorative finish including cleaning washing of surface etc. complete with: On old work (One or more coats applied @ 0.83 ltr/ 10 sqm)Manufractured with the cow dung proccessing	60.00	Sqm
28	Electrification Work As electric SOR 01.06.2020 Lum-Sum		

MM

uantity UCM

कार्यपालन अभियन्ता नगर पालिक निगम, भिलाई

a

े २००७ सहायक अभियन्ता नगर पालिक निगम, भिलाई

) (

उपरेअभियन्ता नगुत्र पालिक निगम, मिलाई