MUNICIPAL CORPORATION BHILAI (C.G.) 3

NIT

कार्य का नाम :- वार्ड क्रमांक 30 प्रगतिनगर केम्प 01 हनुमान मंदिर के पास सार्वजनिक डोम शेड निर्माण

	As per Building SOR 01.01.2015, Elecstric	Qty	Unit
Sno	Particulars Factorial of the particulars of for any other purpose	34.7	The second second
1	Excavation for all types and sizes of foundations, trenches and drains or for any other purpose including disposal of excavated stuff upto 1.5 m lift and lead upto 50m (at least 5m away from		
	the excavated area), including dressing and leveling of pits.	24.34	Cum
		A 7507 7	CO SARRY
2	Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work 1.4.8 (1 cement : 4		
	coarse sand : 8 graded stone aggregate 40mm nominal size).	3.49	Cum
3	Providing and laying nominal mix reinforced cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work 1:11/2:3 (1cement:11/2 coarse sand:3 graded stone aggregate 20 mm nominal size).		
ange territolyses of	Trement 11/2 coarse sand 3 graded stone aggregate 20 mm rounds	12.70	Cum
4	Providing and placing in position reinforcement for R.C.C. work including straightening, cutting, bending, binding etc. complete as per drawings including cost of binding wire in		
	foundation and plinth all complete:	1015.68	Kg
5	Thermo-Mechanically treated bars FE 415 Providing and fixing form work including centring, shuttering, strutting, staging, propping	poli primi Michae una un diventi immeri di diminuti diviga a un	
J	bracing etc. complete and including its removal at all levels, for: Foundations, footings, bases of columns plinth beam, curtain wall in any shape and size and		
	all type of wall below plinth level for foundation	16.80	Sqm
6	sections, trusses and frame work including cutting, hoisting, fixing in position upto a height of sections, trusses and frame work including cutting, hoisting, fixing in position upto a height of sections, trusses and frame work including cutting, hoisting, fixing in position upto a height of sections, trusses and trusses, roof and bottom purlins, base plate, but a put and washers for fastening etc.		
	holding down holts wind ties bracing (if required), bolts, huls and washers for lastering		
	holding down bolts, wind ties bracing (if required), bolts, holts and washers for lastering complete with applying a priming coat of red oxide zinc chromate primer.		
	holding down bolts, wind ties bracing (if required), bolts, holts and washers for lastering complete with applying a priming coat of red oxide zinc chromate primer. Electric resistance or induction butt welded tubes Grade-250	7878.82	kg
7	holding down bolts, wind ties bracing (if required), bolts, nots and washers for lastering complete with applying a priming coat of red oxide zinc chromate primer. Electric resistance or induction butt welded tubes Grade-250 Supply and fixing of precoated galvanized iron profile sheets (size, shapeand pitch of corrugation as approved by Engineer-in-charge) 0.50 mm +/-5% total coated thickness (TCT), Zinc coating 120gsm as per IS: 277 in240mpa steel grade, 5-7 microns epoxy primer on both side of the sheetand polyester top coat 15-18 micronss of size (5.5x 55mm) with EPDM seal or with polymer coated J or L hooks, bolts and nuts 8mm diameter with bitumen and G.I.limpet washers or with G.I. limpet washers filled with white lead completeupto any sitch in horizontal/ vertical or curved surfaces excluding the costof purlins, rafters and trusses		kg
7	holding down bolts, wind ties bracing (if required), bolts, note and washers for lastering complete with applying a priming coat of red oxide zinc chromate primer. Electric resistance or induction butt welded tubes Grade-250 Supply and fixing of precoated galvanized iron profile sheets (size, shapeand pitch of corrugation as approved by Engineer-in-charge) 0.50 mm +/-5% total coated thickness (TCT), Zinc coating 120gsm as per IS: 277 in240mpa steel grade, 5-7 microns epoxy primer on both side of the sheetand polyester top coat 15-18 micronss of size (5.5x 55mm) with EPDM seal or with polymer coated J or L hooks, bolts and nuts 8mm diameter with bitumen	7878.82 172.50	
	holding down bolts, wind ties bracing (if required), bolts, note and washers for lastering complete with applying a priming coat of red oxide zinc chromate primer. Electric resistance or induction butt welded tubes Grade-250 Supply and fixing of precoated galvanized iron profile sheets (size, shapeand pitch of corrugation as approved by Engineer-in-charge) 0.50 mm +/-5% total coated thickness (TCT), Zinc coating 120gsm as per IS: 277 in240mpa steel grade, 5-7 microns epoxy primer on both side of the sheetand polyester top coat 15-18 micronss of size (5.5x 55mm) with EPDM seal or with polymer coated J or L hooks, bolts and nuts 8mm diameter with bitumen and G.I.limpet washers or with G.I. limpet washers filled with white lead completeupto any pitch in horizontal/ vertical or curved surfaces excluding the costof purlins, rafters and trusses and including cutting to size and shape wherever required.		
7	holding down bolts, wind ties bracing (if required), bolts, nots and washers for lastering complete with applying a priming coat of red oxide zinc chromate primer. Electric resistance or induction butt welded tubes Grade-250 Supply and fixing of precoated galvanized iron profile sheets (size, shapeand pitch of corrugation as approved by Engineer-in-charge) 0.50 mm +/-5% total coated thickness (TCT), Zinc coating 120gsm as per IS: 277 in240mpa steel grade, 5-7 microns epoxy primer on both side of the sheetand polyester top coat 15-18 micronss of size (5.5x 55mm) with EPDM seal or with polymer coated J or L hooks, bolts and nuts 8mm diameter with bitumen and G.I.limpet washers or with G.I. limpet washers filled with white lead completeupto any sitch in horizontal/ vertical or curved surfaces excluding the costof purlins, rafters and trusses		kg Sqm
	holding down bolts, wind ties bracing (if required), bolts, note and washers for lastering complete with applying a priming coat of red oxide zinc chromate primer. Electric resistance or induction butt welded tubes Grade-250 Supply and fixing of precoated galvanized iron profile sheets (size, shapeand pitch of corrugation as approved by Engineer-in-charge) 0.50 mm +/-5% total coated thickness (TCT), Zinc coating 120gsm as per IS: 277 in240mpa steel grade, 5-7 microns epoxy primer on both side of the sheetand polyester top coat 15-18 micronss of size (5.5x 55mm) with EPDM seal or with polymer coated J or L hooks, bolts and nuts 8mm diameter with bitumen and G.I.limpet washers or with G.I. limpet washers filled with white lead completeupto any pitch in horizontal/ vertical or curved surfaces excluding the costof purlins, rafters and trusses and including cutting to size and shape wherever required. Extra for providing and fixing wind ties of 40x6mm flat iron section.	172.50 72.00	Sqm
8	holding down bolts, wind ties bracing (if required), bolts, fluts and washers for restarting complete with applying a priming coat of red oxide zinc chromate primer. Electric resistance or induction butt welded tubes Grade-250 Supply and fixing of precoated galvanized iron profile sheets (size, shapeand pitch of corrugation as approved by Engineer-in-charge) 0.50 mm +/-5% total coated thickness (TCT), Zinc coating 120gsm as per IS: 277 in240mpa steel grade, 5-7 microns epoxy primer on both side of the sheetand polyester top coat 15-18 microns	172.50 72.00 120.00	Sqm
	holding down bolts, wind ties bracing (if required), bolts, note and washers for lastering complete with applying a priming coat of red oxide zinc chromate primer. Electric resistance or induction butt welded tubes Grade-250 Supply and fixing of precoated galvanized iron profile sheets (size, shapeand pitch of corrugation as approved by Engineer-in-charge) 0.50 mm +/-5% total coated thickness (TCT), Zinc coating 120gsm as per IS: 277 in240mpa steel grade, 5-7 microns epoxy primer on both side of the sheetand polyester top coat 15-18 micronss of size (5.5x 55mm) with EPDM seal or with polymer coated J or L hooks, bolts and nuts 8mm diameter with bitumen and G.I.limpet washers or with G.I. limpet washers filled with white lead completeupto any pitch in horizontal/ vertical or curved surfaces excluding the costof purlins, rafters and trusses and including cutting to size and shape wherever required. Extra for providing and fixing wind ties of 40x6mm flat iron section.	172.50 72.00	Sqm

सहायके अभियन्ता नगर पालिक निगम, भिलाई

उप असियन्त्रा नगर असिक निगम, भिलाई

Page 1 of 1

101111