MUNICIPAL CORPORATION OF BHILAI

वार्ड 68 सेक्टर 08 सङ्का5,16 के मध्य मिनी उद्यान निर्माण कार्य

As Per PWD Building & Road SOR 01.01.2015, Electrical SOR 01.06.2020 & NON Excavation for all types and sizes of foundations, trenches and the state of foundations, trenches and the state of foundations.		
Excavation for all types and sizes of foundations, trenches and drains or for any other purpose including dressing and leveling of pits. Excavation for all types and sizes of foundations, trenches and drains or for any other purpose including dressing and leveling of pits.		
PARTICULERS OF FIGURE SOR 01.06.2020 & NON	SOP ITEM	
disposal of exeavated stuff upto 1.5 m lift and lead upto 50m (at least 5m away from the excavated Providing and laying nominal mix plain cement concrete with	SORTIEM	
		UOM
Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete excluding cost of form work. 2, 1:4:8 (1 cement: 4 costs.)	52.490	C
mixer in all works upto plinth level 2, excluding cost of form	52.480	Cum
excluding cost of form work.		
1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size). Concrete mixer in all works up to a six of the concrete with crushed stone aggregate 40mm nominal size.		
Providing and laying nominal mix reinforced cement concrete with crushed stone aggregate using excluding cost of form work.	16.000	Cum
concrete mixer in all mix reinforced congrete 40mm nominal size).		
3 excluding cost of form work.		
1:14:3 (Legymont work.		
powing in 1/2 coarse sand : 3 graded at	11.070	Cum
1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm Providing and filling in the same same same same same same same sam		
	i l	
4 exceeding 20cm in depth consolidating each deposited layer by ramming and watering, including Providing & laying 60mm this to		
dressing etc. complete.	30.210	Cum
Providing & laying 60mm thick precast interlocking concrete blocks of approved size (approx 305 filled by fine send in 1 mm thick average complete coarse send had with initial 1 mm.		
sqcm) and shape/ pattern, over 40 mm thick average complete coarse sand bed with joints of 3mm thick including leveling with surface vibrator temping and suggestions of the sand including leveling with surface vibrator temping and suggestions of the sand including leveling with surface vibrator temping and suggestion at the sand including leveling with surface vibrator temping and suggestions at the sand including leveling with surface vibrator temping and suggestions at the sand including leveling with surface vibrator temping and suggestions.		
	ck	
minimum compressive street and system with surface vibrator, temping and sweeping etc. complete of	64.000	cam
minimum compressive strength of 250 kg/sq.cm	04.000	sqm
Plain/ normal coloured precast interlock concrete blocks Providing and placing in position rainforms.		
Providing and placing in position reinforcement for R.C.C. work including straightening, cutting, bending, binding etc. complete as per drawings		
bending, binding etc. complete as per drawings	(2()	1
	626.8	kg
Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work.		
mixer in all works upto plinth level excluding cost of form work.		
	0.68	Cum
Providing and fixing form work including centring, shuttering, strutting, staging, propping bracing etc 8 8 Providing and fixing form work including centring, shuttering, strutting, staging, propping bracing etc		
complete and including this removal at all levels, for:	c.	
Columns, beams & Walls- circular or any other general.	7.68	Cum
all sizes all sizes	ı /.00	Cum
Steel work welded in built up sections/ framed work including a visit to the section of the sect		
applying a priming coat of red oxide zinc	i	
chromate primer. In stringers, treads, landings etc. of stair cases including use of chequered plate		l .
wherever required, all complete.	107.77	kg
Drawid: 1 - 1		
In Cement Morton 14 (1) and thick cement plaster of mix:		
In Cement Mortar 1:4 (1 cement : 4 fine sand)	5.52	sqm
Finishing walls with water proofing cement paint of required shade to give an even shade.		· ·
	5.52	sqm
2 Painting on new work (two or more coats) to give an even shade with:		54
19auli Sviillielic enamel naint	5.10	
Surface dressing of the ground including removing vogetation and the		sqm
and in-equalities not exceeding 15 cms in depth/ height including disposal of rubbish upto 1	ns	
m lift and lead upto 50m (at least 5m away from the dressed area).	.5 81.36	sqm
Providing and laving naminal mix state agent the dressed area).		Sqiii
Providing and laying nominal mix plain cement concrete with crushed		+
Islane aggregate using concrete mixer in all works unto plinth level		
excluding cost of form work. 1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregation)	to 3.05	Cum
140mm nominal size).		5411
Providing and laying nominal mix reinforced cement concrete with crushed stone aggrega		
using concrete mixer in all works upto plinth level excluding cost of form work. 1:11/2:3	te	
compart 11/ pages and 2 graded stars says 122	(1 7.0.	
cement: 1½ coarse sand: 3 graded stone aggregate 20mm nominal size).	7.01	Cum
		, and
Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002	of	
class designation 4.0 in foundation and plinth in:Cement Mortar 1:6 (1 cement : 6 coars		
	se 9.15	Cum
sand)		32
15mm thick cement plaster on the rough side of single or half brick wall of mix:	111.88	Sqm
		i Sam

Providing and placing in position analysis root standard of new work (Three or more code) frowing and placing in position analysis root grow on overn shade. On new work (Three or more code) frowing and placing in position analysis root grows an overn shade. On new work (Two or providing and placing in position analysis root grows and shade and shading policia top on septial and beat an influent analysis in gone and a shade of the providing bodies in 19.7 not on as per requirement including points upon the position with it is consent connect block. In order the position work (two or more code) to give an overn shade with Promism symbotic connections and the providing position work (two or more code) to give an overn shade with Promism symbotic connections and shade on the Providing and Screwing with CI I shap awar, CI shapes, CI Urash or stoot paris side. Supply Of Swaged seel robular Pole as per R 2713 with two place of two poles of man welded Designation 10 specified height including partiting with one coal of sed oxide into effortune primer. I Each Designation 10 specified height from the providing poles in counter connected scalar of seasons and it is provided to grow the provided poles of the poles		washing with whiting to give an over		
De spilt and Dental right angle in opposite one post and strut of required size including bottom to me agree of right angle in opposite direction for required larget and dental politics in the property struth in coment concentration by the do sode zinc chrematis primer and including primer and includin		empering with acrylic washable distanced. On new work (Three or more cost		
10 mm of as per organization of regulated size in classified policies up in placing the poper forgationed interfacional for required length policy up in placing the poper forgationed interfacional promised could will red oxido zinc chromato primary and plants. Providing and fixing in position welded steel were above the promise will be provided and steel provided provided and steel provided provided steel were above to provide a plant in providing and fixing in position welded steel were above to be provided and steel provided provided and steel provided		Providing and placing is	111.88	Sam
Participation posses Strict in comment controls belock considered on New York (two or more coasta) to give an own stande with Prantium synthetic consideration of the Coasta of the Coas		be split and bent at right angle iron post and strut of rowing.		
Participation posses Strict in comment controls belock considered on New York (two or more coasta) to give an own stande with Prantium synthetic consideration of the Coasta of the Coas		10 mm dia as per requirement including bottom to		3911
Cenamed Daller Providing and Kings in position worked steel wire fabric to concretely worder large from position worked steel wire fabric to concretely worder large from position models as seen and secrewing with G. I. pring wire, G.I. stapples, G.I. Il-naits or steel prins (e.g., 183.08) Supply O.I. Wanged steel turbular Pole as sper IS 2713 with base place of size 300 x 3000 x 6 mm welder Decignation 4.10 x 12.0 cheigh 3.00 miles in challing printing with one could for decide from chromate prinner. In the control of the country of the c		Painting the post/ strut in cement concrete black coat with red oxide zinc chromate.	1007.404	Va
Second Section	1	enamel paint work (two or more coals) to give	1007.101	Ng
Second Section	1	Providing and fixing in many to give an even shade with: Premium synthetic		-
Supply Of Named steel dublate Pole as per IS 2713 with base plate of \$2x 300 x 3000 x 6 mm veided Designation 410 SP_26 height 90 Breach Exection of STEEL 1 URL AR or "I" BEAM ISSME pole in center of coats a fired oxide zinc chromate primer. 1		including securing and screwing	368.62	Sqm
Supply Of Named steel dublate Pole as per IS 2713 with base plate of \$2x 300 x 3000 x 6 mm veided Designation 410 SP_26 height 90 Breach Exection of STEEL 1 URL AR or "I" BEAM ISSME pole in center of coats a fired oxide zinc chromate primer. 1	-	complete grand screwing with G.I. tying wire, G.I. staples, G.I.L-nails or steel in		
Erection of STEEL TUDULAR or "I" BEAM/ ISMB pole in cement concrete 13.6 (1 cement : 3 size 0.4 metre dia and 0.50 metre legal from ground level including excavation and refilling etc. as per Supplying and Tising water right terminal hox made of 1.6mm thick M.S. sheet with detachable gland plate in bottom, hinged front open able cover, rubber gasket, having 1 Nos 4way connector and 1 No flat with 2.5 No nut bolt dully painted with 2 cost of red oxide paint and 2 cost aluminium paint complete as a per specification. Supplying and making end termination with brass compression gland and aluminium paint complete as supplying and making end termination with brass compression gland and aluminium paint complete as supplying and making end termination with brass compression gland and aluminium paint complete as supplying and making end termination with brass compression gland and aluminium ges for following 2.5 mm. Supplying and making end termination with brass compression gland and aluminium uses for following 2.5 mm. Supplying and making end termination with brass compression gland and aluminium uses for following 2.5 mm. Supplying and fixing & cramping suitable size & all type aluminium fortule/lugs for following size 1.1 KV grade power enable core/lead pressed with high pressure cramping tool including connection to switch gear/MCCB etc as required 2.5 sq.nmm. Liem = 17.2.8.4 Supplying and fixing G.I. pipe along with wall or pole/ support with 2 Nos MS clamps for protection of under ground cable in approved manner including bolts and nuts or metal dash fusteners complete with supply of material labour cie, including preparation of surface. Painting new steel and other metallic surface with red oxide zinc chromide prime paint complete with 6.3 Sqm supply of material labour cie, including preparation of surface. Supply and fixing following suried light pole bracket on existing pole made out of 50 mm dia MS "B" class pipe welded to 300 mm long MS pole canopy of suitable dia at a angle of 102.50 including havin		Toubbly Of Swaper at the state of steel pins etc. 1	183.08	Sqm
Erection of STEEL TUDULAR or "I" BEAM/ ISMB pole in cement concrete 13.6 (1 cement : 3 size 0.4 metre dia and 0.50 metre legal from ground level including excavation and refilling etc. as per Supplying and Tising water right terminal hox made of 1.6mm thick M.S. sheet with detachable gland plate in bottom, hinged front open able cover, rubber gasket, having 1 Nos 4way connector and 1 No flat with 2.5 No nut bolt dully painted with 2 cost of red oxide paint and 2 cost aluminium paint complete as a per specification. Supplying and making end termination with brass compression gland and aluminium paint complete as supplying and making end termination with brass compression gland and aluminium paint complete as supplying and making end termination with brass compression gland and aluminium paint complete as supplying and making end termination with brass compression gland and aluminium ges for following 2.5 mm. Supplying and making end termination with brass compression gland and aluminium uses for following 2.5 mm. Supplying and making end termination with brass compression gland and aluminium uses for following 2.5 mm. Supplying and fixing & cramping suitable size & all type aluminium fortule/lugs for following size 1.1 KV grade power enable core/lead pressed with high pressure cramping tool including connection to switch gear/MCCB etc as required 2.5 sq.nmm. Liem = 17.2.8.4 Supplying and fixing G.I. pipe along with wall or pole/ support with 2 Nos MS clamps for protection of under ground cable in approved manner including bolts and nuts or metal dash fusteners complete with supply of material labour cie, including preparation of surface. Painting new steel and other metallic surface with red oxide zinc chromide prime paint complete with 6.3 Sqm supply of material labour cie, including preparation of surface. Supply and fixing following suried light pole bracket on existing pole made out of 50 mm dia MS "B" class pipe welded to 300 mm long MS pole canopy of suitable dia at a angle of 102.50 including havin		at bottom specified height including painting with one plate of size 300 x 3000 x 6 mm welded		
coarse sand : 6 graded stone agergate 40 nm nominal size) foundation and cement concrete 13:6 (1 coment : 3 secification of length: 7 metre to 10 metre height from ground level including excavation and refliking etc. as per Supplying and fixing water right terminal box made of 1.6mm thick M.S. sheet with detachable gland plate in bottom, highed front open able cover, rubber gasket, having 1 Nos 4way connector and 1 No flat with 2 No nut bott dulty painted with 2 coat of red oxide paint and 2 coat aluminium paint complete 3 sper specification. SYMC6 inside the box for cable connection, fixed to pole with 2 Nos elamp made from 483-mm M.S. as per specification. Sypplying and making end termination with brass compression gland and aluminium paint complete 3 sper specification. Supply fixed fixing & cramping suitable size & all type aluminum ferule/lugs for following size 1.1 KV grade sper specification. Sypplying and fixing 6.1 pipe along with wall or pole/ support with 2 Nos MS clamps for protection of under ground cable in approved manner including botts and mats or metal dash fasteners complete as per specification. 32 mm dia Painting new steel and other metallic surface with red oxide zinc chromide primer paint complete with supply of material labour etc. including preparation of surface. Supply and fixing following street light pole bracket on existing pole made out of 50 mm dia MS "B" class pipe welded to 300 mm long MS pole canopy of suitable dia at a mgle of 102.50 including laving with supprive of size 15 N S OX S mm thick, making arrangement for tightening the bracket with pole by providing suitable size heavy duty nuts and botts in canopy, painting with one coat of approved steel primer etc. as per specification. Double Over Hang 1.50 metre Long Pointing wood steel and other metallic surface with Aluminium Paint complete with material and labour including preparation of surface. Providing and laying Cast-in-situ cement concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded stone approved steel primer	-	Erection of STEEL Theorem 9.00 metre	1	Each
seccification of femals. 7 metre to 10 metre Supplying and fixing water tight terminal box made of 1.6mm thick M.S. sheet with denochable gland SPMCB inside the box for cable connection, fixed to pole with 2 Nos Away connector and 1 No flaw with 2 No nut bott dully painted with 2 coat of red oxide paint and 2 coat aluminium paint complete 30 x 20 x 15 cms Supplying and making end termination with brass compression gland and aluminum lugs for following size armoured aluminum conductor power cable of 1.1 KV grade as per specification. 3 x 25 sq. mm Supplying and making end termination with brass compression gland and aluminum lugs for following size armoured aluminum conductor power cable of 1.1 KV grade as per specification. 3 x 25 sq. mm Supplying and making end termination with brass compression gland and aluminum lugs for following size armoured aluminum conductor power cable of 1.1 KV grade as per specification. 3 x 25 sq. mm Supplying and fixing G.I. pipe along with wall or pole/ support with 2 Nos MS clamps for protection of under ground cable in approved manner including bolts and nuts or metal dash fasteners complete as per specification. 32 mm dia Painting new steel and other metallic surface with red oxide zinc chromide primer paint complete with supply of material labour etc. including preparation of surface Supply and fixing Gollowing street light pole bracket on existing pole made out of 50 mm dia MS "B" class pipe welded to 300 mm long MS pole canopy of suitable dia at a angle of 102.50 including having MS triangular stiffner of size 150 x 50 x 5 mm thick, making arrangement for tightening the bracket with pole by providing suitable size heavy duty nuts and bolts in canopy, painting with one coat of approved steel primer etc. as per specification. Double Over Hang 1.50 metre Long Providing and laying Cast-in-situ coment concrete vork at all levels including removing of the same. Providing and laying Cast-in-situ coment concrete work at all levels including removing of the same. Providing ti		coarse sand: 6 graded at		
Supplying and Tixing water tight terminal box made of 1.6mm thick M.S. sheet with detachable gland SPANCB inside the box for enbet connection, fixed to pole with 2 Nos clamp made from 40x3mm M.S. as per specification. 25 SPNCB inside the box for enbet connection, fixed to pole with 2 Nos clamp made from 40x3mm M.S. as per specification. 26 Supplying and making end termination with brass compression gland and aluminium paint complete size armoured aluminium conductor power cable of 1.1 KV grade as per specification. 27 Supply & fixing & cramping suitable size & all type aluminum ferule/lugs for following size 1.1 KV grade power cable core/lead pressed with high pressure cramping tool including connection to switch gear/MCCB etc as required 25 sq.mm. 28 Supplying and fixing G.I. pipe along with wall or pole/ support with 2 Nos MS clamps for protection of underground cable in approved manner including bolts and nuts or metal dash fasteners complete as per specification. 32 mm dia 29 Painting new steel and other metallic surface with red oxide zinc chromide primer paint complete with supply of material labour etc. including preparation of surface. 29 Supply and fixing following street light pole bracket on existing pole made out of 50 mm dia MS "B" class pipe welded to 300 mm long MS pole canopy of suitable dia at a angle of 102.50 including having MS triangular stiffner of size 150 x 50 x 5 mm thick, making arrangement for tightening the bracket with pole by providing suitable size heavy duty nuts and bolts in canopy, painting with one coat of approved steel primer etc. as per specification. Double Over Hang 1.50 metre Long 31 Painting wood steel and other metallic surface with Aluminium Paint complete with material and labour including preparation of surface. 32 Providing and laying Cast-in-situ cement concrete 1:3:6 (I cement : 3 coarse sand : 6 graded stone aggregate 40mm including mixing with mechanical mixer, compacting with vibrator, finishing and aggregate 40mm including mixing with mechanical mixer			1	
plate in bottom, linged front open able cover, rubber gasket, having 1 Nos dway connector and 1 No flat with 2 No not both dully painted with 2 Cont of red oxide paint and 2 coat aluminium paint complete as per specification. 25 Supplying and making end termination with brass compression gland and aluminium paint complete size armoured aluminium conductor power cable of 1.1 KV grade as per specification. 3 x 2.0 x 15 cm. Supplying and making end termination with brass compression gland and aluminium logs for following size armoured aluminium conductor power cable of 1.1 KV grade as per specification. 3 x 25 sq. mm Supply & fixing & cramping suitable size & all type aluminium ferule/lugs for following size 1.1 KV grade as per specification. 3 x 25 sq. mm Supply & fixing & cramping suitable size & all type aluminium ferule/lugs for following size 1.1 KV grade as per specification. 3 x 25 sq. mm Litem - 17.2 kd. Supplying and fixing G.1. pipe along with wall or pole/ support with 2 Nos MS clamps for protection of under ground cable in approved manner including bolts and nuts or metal dnsh fasteners complete as per specification. 3 2 mm dia Painting new steel and other metallic surface with red oxide zinc chromide primer paint complete with supply of material labour etc. including preparation of surface Supply and fixing following street light pole bracket on existing pole made out of 50 mm dia MS "B" class pipe welded to 300 mm long MS pole canopy of suitable dia at a nagle of 102.50 including having MS triangular stiffner of size 150 X 50 X 5 mm thick, making arrangement for tightening with one coat of approved steel primer etc. as per specification. Double Over Hang 1.50 metre Long Providing and laving Cast-in-situ cement concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40mm including mixing with mechanical mixer, compacting with vibrator, finishing and aggregate 40mm including mixing with mechanical mixer, compacting with vibrator, finishing and gaggregate form work for cement concre	_	- Proceeding CACGAMION and February of the second of the s	1	Each
SPANCB inside the box for cable connection, fixed to pole with 2 Nos to Nos damy mode from 40x3mm M.S. as per specification. 30 x 20 x 15 cms	1	They mig and fixing Water tight town:		
SPANCB inside the box for cable connection, fixed to pole with 2 Nos to Nos damy mode from 40x3mm M.S. as per specification. 30 x 20 x 15 cms		plate in bottom, hinged front open able cover, rubber gradest basis and the state with detachable gland		
as per specification. 30 x 20 x 15 cms Supplying and making end termination with brass compression gland and aluminum lugs for following size armounced aluminum conductor power cable of 1.1 KV grade as per specification.3 X 25 sq. mm Supply & fixing & cramping suitable size & all type aluminum ferule/fugs für following size 1.1 KV grade power cable core/lead pressed with high pressure cramping tool including connection to switch grade power cable core/lead pressed with high pressure cramping tool including connection to switch grade power cable core/lead pressed with high pressure cramping tool including connection to switch grade power cable core/lead pressed with high pressure cramping tool including connection to switch gear/MCCB etc as required 25 sq.nm. Item - 17.28.4 Supplying and fixing G.I. pipe along with wall or pole/ support with 2 Nos MS clamps for protection of under ground cable in approved manner including bolts and nuts or metal dash fasteners complete as per specification. 32 mm dia Painting new steel and other metallic surface with red oxide zinc chromide primer paint complete with grade per specification. 32 mm dia MS "B" Class pipe welded to 300 mm long MS pole canopy of suitable dia at a angle of 102.50 including having MS triangular stiffner of size 150 X 50 X 5 mm thick, making arrangement for tightening the bracket with pole by providing suitable size heavy duty nuts and bolts in canopy, painting with one coat of approved steel primer etc. as per specification. Double Over Hang 1.50 metre Long Painting wood steel and other metallic surface with Aluminium Paint complete with material and labour including preparation of surface. Providing and laying Cast-in-situ cement concrete 1:36 (1 cement : 3 conres sand : 6 graded stone aggregate 40mm including mixing with mechanical mixer, compacting with vibrator, finishing and aggregate 40mm including mixing with mechanical mixer, compacting with vibrator, finishing and aggregate 40mm including form work. Providing timber / steel form work	2	55 SPMCB inside the box for cable connection of Spacet, flaving 1 Nos 4way connector and 1 No		
30 x 20 x 15 cms Supplying and making end termination with brass compression gland and aluminum lugs for following size armoured aluminum conductor power cable of 1.1 KV grade as per specification.3 X 25 sq. mm 3		flat with 2 No nut bolt dully painted with 2 coat of red oxide paint and 2 coat aluminium point count late.	I	Each
Supplying and making end termination with brass compression gland and aluminum lugs for following size armoured aluminum conductor power cable of 1.1 KV grade as per specification.3 X 25 sq. mm Supply & fixing & cramping suitable size & all type aluminum ferule/lugs for following size 1.1 KV grade power cable core/lead pressed with high pressure cramping tool including connection to switch grade power cable core/lead pressed with high pressure cramping tool including connection to switch grade power cable core/lead pressed with high pressure cramping tool including connection to switch grade power cable core/lead pressed with high pressure cramping tool including connection to switch grady flower grade proved manner including bolts and nuts or metal dash fusteners complete as per specification. 32 mm dia Painting new steel and other metallic surface with red oxide zinc chromide primer paint complete with supply of material labour etc. including preparation of surface Supply and fixing following street light pole bracket on existing pole made out of 50 mm dia MS "B" class pipe welded to 300 mm long MS pole canopy of suitable dia at a angle of 102.50 including having MS triangular stiffner of size 150 X 50 X 5 mm thick, making arrangement for tightening the bracket with pole by providing suitable size heavy duty nuts and bolts in canopy, painting with one coat of approved steel primer etc. as per specification. Double Over Hang 1.50 metre Long Painting wood steel and other metallic surface with Aluminium Paint complete with material and labour including preparation of surface. Providing and laying Cast-in-situ cement concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40mm including mixing with mechanical mixer, compacting with vibrator, finishing and o.25 Cum aggregate 40mm including mixing with mechanical mixer, compacting with vibrator, finishing and o.25 Sqm Earthing with G.I. carth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover plate hav		as per specification.		
C25 mm		Supplying and making and town in the supplying and making and town in the supplying and making and town in the supplying and supplying an accordance and supplying a sup		
C25 mm	2	6 size armoured aluminum conductor review 11 c		
gear/MCCB etc as required 25 sq.nm. tem - 17.28.4			3	Each
gear/MCCB etc as required 25 sq.mm. tem - 17.28.4 Supplying and fixing G.I. pipe along with wall or pole/ support with 2 Nos MS clamps for protection of under ground cable in approved manner including bolts and nuts or metal dash fasteners complete as per specification. 32 mm dia Painting new steel and other metallic surface with red oxide zinc chromide primer paint complete with supply of material labour etc. including preparation of surface Supply and fixing following street light pole bracket on existing pole made out of 50 mm dia MS "B" class pipe welded to 300 mm long MS pole canopy of suitable dia at a angle of 102.50 including having MS triangular stiffner of size 150 X 50 X 5 mm thick, making arrangement for tightening the bracket with pole by providing suitable size heavy duty nuts and bolts in canopy, painting with one coat of approved steel primer etc. as per specification. Double Over Hang 1.50 metre Long Painting wood steel and other metallic surface with Aluminium Paint complete with material and labour including preparation of surface.		Supply & fixing & cramping suitable size & all type aluminum ferule/lugs for following size 1.1 KV		
Supplying and fixing G.I. pipe along with wall or pole/ support with 2 Nos MS clamps for protection of under ground cable in approved manner including bolts and nuts or metal dash fasteners complete as per specification. 32 mm dia	2	7 Island power cable core/lead pressed with high pressure cramping tool including connection to switch.	_	
Supplying and fixing G.I. pipe along with wall or pole/ support with 2 Nos MS clamps for protection of under ground eable in approved manner including bolts and nuts or metal dash fasteners complete as per specification. 32 mm dia Painting new steel and other metallic surface with red oxide zinc chromide primer paint complete with supply of material labour etc. including preparation of surface Supply and fixing following street light pole bracket on existing pole made out of 50 mm dia MS "B" class pipe welded to 300 mm long MS pole canopy of suitable dia at a angle of 102.50 including having MS triangular stiffner of size 150 X 50 X 5 mm thick, making arrangement for tightening the bracket with pole by providing suitable size heavy duty nuts and bolts in canopy, painting with one coat of approved steel primer etc. as per specification. Double Over Hang 1.50 metre Long Painting wood steel and other metallic surface with Aluminium Paint complete with material and labour including preparation of surface. Providing and laying Cast-in-situ cement concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40mm including mixing with mechanical mixer, compacting with vibrator, finishing and aggregate 40mm including mixing with mechanical mixer, compacting with vibrator, finishing and currying etc. complete but excluding form work. Providing timber / steel form work for cement concrete work at all levels including removing of the same. Earthing with G.I. earth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as enclosure with cover plate having locking arrangement and watering	-	geat/MCCB etc as required 25 sq.mm.	2	Each
under ground cable in approved manner including bolts and nuts or metal dash fasteners complete as per specification. 32 mm dia 29 Painting new steel and other metallic surface with red oxide zinc chromide primer paint complete with supply of material labour etc. including preparation of surface Supply and fixing following street light pole bracket ton existing pole made out of 50 mm dia MS "B" class pipe welded to 300 mm long MS pole canopy of suitable dia at a angle of 102.50 including having MS triangular stiffher of size 150 X 50 X 5 mm thick, making arrangement for tightening the bracket with pole by providing suitable size heavy duty nuts and bolts in canopy, painting with one coat of approved steel primer etc. as per specification. Double Over Hang 1.50 metre Long 31 Painting wood steel and other metallic surface with Aluminium Paint complete with material and labour including preparation of surface. Providing and laying Cast-in-situ cement concrete 1:3:6 (1 cement: 3 coarse sand: 6 graded stone agreegate 40mm including mixing with mechanical mixer, compacting with vibrator, finishing and currying etc. complete but excluding form work. Providing timber / steel form work for cement concrete work at all levels including removing of the existing surface / steel form work for cement concrete work at all levels including removing of the enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as enclosure with cover plate having locking arrangement and watering pain etc. with charcoal and salt as enclosure with cover plate having locking arrangement and watering pain etc. with charcoal and salt as enclosure with cover plate having locking arrangement and watering pape etc. with charcoal and salt as enclosure with cover plate having locking arrangement and wate	-			
Painting new steel and other metallic surface with red oxide zinc chromide primer paint complete with supply of material labour etc. including preparation of surface Supply and fixing following street light pole bracket on existing pole made out of 50 mm dia MS "B" class pipe welded to 300 mm long MS pole canopy of suitable dia at a angle of 102.50 including having MS triangular stiffner of size 150 X 50 X 5 mm thick, making arrangement for tightening the bracket with pole by providing suitable size heavy duty nuts and bolts in canopy, painting with one coat of approved steel primer etc. as per specification. Double Over Hang 1.50 metre Long Painting wood steel and other metallic surface with Aluminium Paint complete with material and labour including preparation of surface. Providing and laying Cast-in-situ cement concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40mm including mixing with mechanical mixer, compacting with vibrator, finishing and currying etc. complete but excluding form work. Providing timber / steel form work for cement concrete work at all levels including removing of the same. Earthing with G.I. carth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and Sc Code 3043: 1987(R 2016) Supplying and drawing following sizes of FRLS PVC insulated copper conductor, multi strand wire in Supplying and drawing following sizes of FRLS PVC conduit / PVC casing caping as per specification and IS: the existing surface/ concealed, FRLS PVC conduit / PVC casing caping as per specification and IS: the existing surface/ concealed, FRLS PVC conduit / PVC casing caping as per specification and IS: the existing surface/ concealed, FRLS PVC conduit / PVC casing caping as		Supplying and fixing G.I. pipe along with wall or pole/ support with 2 Nos MS clamps for protection of		1
Painting new steel and other metallic surface with red oxide zinc chromide primer paint complete with supply of material labour etc. including preparation of surface Supply and fixing following street light pole bracket on existing pole made out of 50 mm dia MS "B" class pipe welded to 300 mm long MS pole canopy of suitable dia at a angle of 102.50 including having MS triangular stiffner of size 150 X 50 X 5 mm thick, making arrangement for tightening the bracket with pole by providing suitable size heavy duty nuts and bolts in canopy, painting with one coat of approved steel primer etc. as per specification. Double Over Hang 1.50 metre Long Painting wood steel and other metallic surface with Aluminium Paint complete with material and labour including preparation of surface. Providing and laying Cast-in-situ cement concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40mm including mixing with mechanical mixer, compacting with vibrator, finishing and currying etc. complete but excluding form work. Providing timber / steel form work for cement concrete work at all levels including removing of the same. Earthing with G.I. earth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as the existing surface/ concealed, FRLS PVC conduit / PVC casing caping as per specification and IS: Sqm Sqm 1 Set Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit	28	under ground cable in approved manner including bolts and nuts or metal dash fasteners complete as	50	Meter
supply of material labour etc. including preparation of surface Supply and fixing following street light pole bracket on existing pole made out of 50 mm dia MS "B" class pipe welded to 300 mm long MS pole canopy of suitable dia at a angle of 102.50 including having MS triangular stiffner of size 150 X 50 X 5 mm thick, making arrangement for tightening the bracket with pole by providing suitable size heavy duty nuts and bolts in canopy, painting with one coat of approved steel primer etc. as per specification. Double Over Hang 1.50 metre Long Painting wood steel and other metallic surface with Aluminium Paint complete with material and labour including preparation of surface. Providing and laying Cast-in-situ cement concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40mm including mixing with mechanical mixer, compacting with vibrator, finishing and currying etc. complete but excluding form work. Providing timber / steel form work for cement concrete work at all levels including removing of the same. Earthing with G.I. carth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as per specification and IS Code 3043: 1987(R 2016) Supplying and drawing following sizes of FRLS PVC insulated copper conductor, multi strand wire in Supplying and drawing following sizes of FRLS PVC conduit / PVC casing caping as per specification and IS: 694 (2010). 3 x 2.50 sq.mm Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling		per specification. 32 mm dia		
supply of material labour etc. including preparation of surface Supply and fixing following street light pole bracket on existing pole made out of 50 mm dia MS "B" class pipe welded to 300 mm long MS pole canopy of suitable dia at a angle of 102.50 including having MS triangular stiffner of size 150 X 50 X 5 mm thick, making arrangement for tightening the bracket with pole by providing suitable size heavy duty nuts and bolts in canopy, painting with one coat of approved steel primer etc. as per specification. Double Over Hang 1.50 metre Long Painting wood steel and other metallic surface with Aluminium Paint complete with material and labour including preparation of surface. Providing and laying Cast-in-situ cement concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40mm including mixing with mechanical mixer, compacting with vibrator, finishing and currying etc. complete but excluding form work. Providing timber / steel form work for cement concrete work at all levels including removing of the same. Earthing with G.I. carth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as per specification and IS Code 3043: 1987(R 2016) Supplying and drawing following sizes of FRLS PVC insulated copper conductor, multi strand wire in Supplying and drawing following sizes of FRLS PVC conduit / PVC casing caping as per specification and IS: 694 (2010). 3 x 2.50 sq.mm Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling	20	Painting new steel and other metallic surface with red oxide zinc chromide primer paint complete with		2
Supply and fixing following street light pole bracket on existing pole made out of 50 mm dia MS "B" class pipe welded to 300 mm long MS pole canopy of suitable dia at a angle of 102.50 including having MS triangular stiffner of size 150 X 50 X 5 mm thick, making arrangement fightening the bracket with pole by providing suitable size heavy duty nuts and bolts in canopy, painting with one coat of approved steel primer etc. as per specification. Double Over Hang 1.50 metre Long Painting wood steel and other metallic surface with Aluminium Paint complete with material and labour including preparation of surface. Providing and laying Cast-in-situ cement concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40mm including mixing with mechanical mixer, compacting with vibrator, finishing and currying etc. complete but excluding form work. Providing timber / steel form work for cement concrete work at all levels including removing of the same. Earthing with G.I. earth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as per specification and IS Code 3043: 1987(R 2016). Supplying and drawing following sizes of FRLS PVC insulated copper conductor, multi strand wire in Supplying and drawing following sizes of FRLS PVC casing caping as per specification and IS: 694 (2010), 3 x 2.50 sq.mm Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling	29	supply of material labour etc. including preparation of surface	6.3	Sqm
MS triangular stiffner of size 150 X 50 X 5 mm thick, making arrangement for tightening the bracket with pole by providing suitable size heavy duty nuts and bolts in canopy, painting with one coat of approved steel primer etc. as per specification. Double Over Hang 1.50 metre Long Painting wood steel and other metallic surface with Aluminium Paint complete with material and labour including preparation of surface. Providing and laying Cast-in-situ cement concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40mm including mixing with mechanical mixer, compacting with vibrator, finishing and currying etc. complete but excluding form work. Providing timber / steel form work for cement concrete work at all levels including removing of the same. Earthing with G.I. carth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as per specification and IS Code 3043: 1987(R 2016) Supplying and drawing following sizes of FRLS PVC insulated copper conductor, multi strand wire in Supplying and drawing following sizes of FRLS PVC insulated copper conductor, multi strand wire in 694 (2010). 3 x 2.50 sq.mm Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit		Supply and fixing following street light pole bracket on existing pole made out of 50 mm dia MS "B"		
with pole by providing suitable size heavy duty nuts and bolts in canopy, painting with one coat of approved steel primer etc. as per specification. Double Over Hang 1.50 metre Long Painting wood steel and other metallic surface with Aluminium Paint complete with material and labour including preparation of surface. Providing and laying Cast-in-situ cement concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40mm including mixing with mechanical mixer, compacting with vibrator, finishing and currying etc. complete but excluding form work. Providing timber / steel form work for cement concrete work at all levels including removing of the same. Earthing with G.I. earth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as per specification and IS Code 3043: 1987(R 2010). Supplying and drawing following sizes of FRLS PVC insulated copper conductor, multi strand wire in the existing surface/ concealed, FRLS PVC conduit / PVC casing caping as per specification and IS: Sqm Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling holes on the board, screws, connections etc. as per specification. (Thimbeling shall be paid separately).		class pipe welded to 300 mm long MS pole canopy of suitable dia at a angle of 102.50 including having		
with pole by providing suitable size heavy duty nuts and bolts in canopy, painting with one coat of approved steel primer etc. as per specification. Double Over Hang 1.50 metre Long Painting wood steel and other metallic surface with Aluminium Paint complete with material and labour including preparation of surface. Providing and laying Cast-in-situ cement concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40mm including mixing with mechanical mixer, compacting with vibrator, finishing and currying etc. complete but excluding form work. Providing timber / steel form work for cement concrete work at all levels including removing of the same. Earthing with G.I. earth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as per specification and IS Code 3043: 1987(R 2016) Supplying and drawing following sizes of FRLS PVC insulated copper conductor, multi strand wire in Supplying and drawing following sizes of FRLS PVC casing caping as per specification and IS: 18 Sqm Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board incl	30	MS triangular stiffner of size 150 X 50 X 5 mm thick, making arrangement for tightening the bracket	2	Each
Painting wood steel and other metallic surface with Aluminium Paint complete with material and labour including preparation of surface. Providing and laying Cast-in-situ cement concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40mm including mixing with mechanical mixer, compacting with vibrator, finishing and currying etc. complete but excluding form work. Providing timber / steel form work for cement concrete work at all levels including removing of the same. Earthing with G.I. earth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as per specification and IS Code 3043: 1987(R 2016) Supplying and drawing following sizes of FRLS PVC insulated copper conductor, multi strand wire in Supplying and drawing following sizes of FRLS PVC conduit / PVC casing caping as per specification and IS: 18 Sqm Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse car		with pole by providing suitable size heavy duty nuts and boits in canopy, painting with one coat of		
labour including preparation of surface. Providing and laying Cast-in-situ cement concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40mm including mixing with mechanical mixer, compacting with vibrator, finishing and currying etc. complete but excluding form work. Providing timber / steel form work for cement concrete work at all levels including removing of the same. Earthing with G.I. earth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as 1 Set per specification and IS Code 3043: 1987(R 2016) Supplying and drawing following sizes of FRLS PVC insulated copper conductor, multi strand wire in Supplying and drawing following sizes of FRLS PVC casing caping as per specification and IS: 18 Sqm (2010). 3 x 2.50 sq.mm Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling holes on the board, screws, connections etc. as per specification. (Thimbeling shall be paid separately). 1 Each		approved steel primer etc. as per specification. Double Over Hang 1.50 metre Long		
labour including preparation of surface. Providing and laying Cast-in-situ cement concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40mm including mixing with mechanical mixer, compacting with vibrator, finishing and currying etc. complete but excluding form work. Providing timber / steel form work for cement concrete work at all levels including removing of the same. Earthing with G.I. earth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as 1 Set per specification and IS Code 3043: 1987(R 2016) Supplying and drawing following sizes of FRLS PVC insulated copper conductor, multi strand wire in Supplying and drawing following sizes of FRLS PVC casing caping as per specification and IS: 18 Sqm (2010). 3 x 2.50 sq.mm Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling holes on the board, screws, connections etc. as per specification. (Thimbeling shall be paid separately). 1 Each		Printing wood steel and other metallic surface with Aluminium Paint complete with material and		
Providing and laying Cast-in-situ cement concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40mm including mixing with mechanical mixer, compacting with vibrator, finishing and currying etc. complete but excluding form work. Providing timber / steel form work for cement concrete work at all levels including removing of the same. Earthing with G.I. earth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as per specification and IS Code 3043: 1987(R 2016) Supplying and drawing following sizes of FRLS PVC insulated copper conductor, multi strand wire in the existing surface/ concealed, FRLS PVC conduit / PVC casing caping as per specification and IS: 18 Sqm Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling holes on the board, screws, connections etc. as per specification. (Thimbeling shall be paid separately).	31	1. Leaving trading propagation of surface	6.3	Sqm
aggregate 40mm including mixing with mechanical mixer, compacting with vibrator, finishing and currying etc. complete but excluding form work. Providing timber / steel form work for cement concrete work at all levels including removing of the same. Earthing with G.I. earth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as supplying and drawing following sizes of FRLS PVC insulated copper conductor, multi strand wire in Supplying and drawing following sizes of FRLS PVC casing caping as per specification and IS: Sqm the existing surface/ concealed, FRLS PVC conduit / PVC casing caping as per specification and IS: 18 Sqm 694 (2010). 3 x 2.50 sq.mm Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling holes on the board, screws, connections etc. as per specification. (Thimbeling shall be paid separately).		Describing and laying Cast-in-situ cement concrete 1:3:6 (1 cement: 3 coarse sand: 6 graded stone		
currying etc. complete but excluding form work. Providing timber / steel form work for cement concrete work at all levels including removing of the same. Earthing with G.I. earth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as per specification and IS Code 3043: 1987(R 2016) Supplying and drawing following sizes of FRLS PVC insulated copper conductor, multi strand wire in the existing surface/ concealed, FRLS PVC conduit / PVC casing caping as per specification and IS: 18 Sqm 694 (2010). 3 x 2.50 sq.mm Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling holes on the board, screws, connections etc. as per specification. (Thimbeling shall be paid separately).	32	recognized 40mm including mixing with mechanical mixer, compacting with vibrator, finishing and	0.25	Cum
Providing timber / steel form work for cement concrete work at an levels including of the same. Earthing with G.I. earth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as per specification and IS Code 3043: 1987(R 2016) Supplying and drawing following sizes of FRLS PVC insulated copper conductor, multi strand wire in the existing surface/ concealed, FRLS PVC conduit / PVC casing caping as per specification and IS: the existing surface/ concealed, FRLS PVC conduit / PVC casing caping as per specification and IS: holes on the board, screws, connections etc. as per specification. (Thimbeling shall be paid separately).	32	1 P Famer work		
Earthing with G.I. carth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry Earthing with G.I. carth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as 1 Set Supplying and drawing following sizes of FRLS PVC insulated copper conductor, multi strand wire in Supplying and drawing following sizes of FRLS PVC casing caping as per specification and IS: 18 Sqm 694 (2010). 3 x 2.50 sq.mm Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling holes on the board, screws, connections etc. as per specification. (Thimbeling shall be paid separately).		Providing timber / steel form work for cement concrete work at all levels including removing of the	2.83	Sam
enclosure with cover plate having locking arrangement and watering paper etc. per specification and IS Code 3043: 1987(R 2016) Supplying and drawing following sizes of FRLS PVC insulated copper conductor, multi strand wire in the existing surface/ concealed, FRLS PVC conduit / PVC casing caping as per specification and IS: the existing surface/ concealed, FRLS PVC conduit / PVC casing caping as per specification and IS: 18 Sqm 694 (2010). 3 x 2.50 sq.mm Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling holes on the board, screws, connections etc. as per specification. (Thimbeling shall be paid separately).	33		2.05	Sqiii
enclosure with cover plate having locking arrangement and watering paper etc. per specification and IS Code 3043: 1987(R 2016) Supplying and drawing following sizes of FRLS PVC insulated copper conductor, multi strand wire in the existing surface/ concealed, FRLS PVC conduit / PVC casing caping as per specification and IS: the existing surface/ concealed, FRLS PVC conduit / PVC casing caping as per specification and IS: 18 Sqm 694 (2010). 3 x 2.50 sq.mm Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling holes on the board, screws, connections etc. as per specification. (Thimbeling shall be paid separately).		Earthing with G.I. earth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry		,
per specification and IS Code 3043: 1987(R 2016) Supplying and drawing following sizes of FRLS PVC insulated copper conductor, multi strand wire in Supplying and drawing following sizes of FRLS PVC casing caping as per specification and IS: 18 Sqm (694 (2010). 3 x 2.50 sq.mm Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling holes on the board, screws, connections etc. as per specification. (Thimbeling shall be paid separately).	34	lenclosure with cover plate having locking arrangement and watering papered.	1	Set
Supplying and drawing following sizes of FRLS I VC institutes FT the existing surface/ concealed, FRLS PVC conduit / PVC casing caping as per specification and IS: 18 Sqm 694 (2010). 3 x 2.50 sq.mm Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling holes on the board, screws, connections etc. as per specification. (Thimbeling shall be paid separately). 1 Each		per specification and IS Code 3043: 1987(R 2016)		
the existing surface/ concealed, FRLS PVC conduit/ TVC entang TC 694 (2010). 3 x 2.50 sq.mm Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling holes on the board, screws, connections etc. as per specification. (Thimbeling shall be paid separately).		Supplying and drawing following sizes of FRLS PVC insulated copper conductor, that it stand whe in	10	
694 (2010). 3 x 2.50 sq.mm Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden board including drilling Back	35	Ithe existing surface/ concealed, FRLS PVC conduit? TVC change	10	Sqm
holes on the board, screws, connections etc. as per special between the board screws, connections etc. as per special between the board screws, connections etc. as per special between the board screws, connections etc. as per special between the board screws are the board screws and the board screws are the board screws.		1694 (2010), 3 x 2.50 sq.mm		
holes on the board, screws, connections etc. as per special between the board screws, connections etc. as per special between the board screws, connections etc. as per special between the board screws, connections etc. as per special between the board screws are the board screws and the board screws are the board screws.		Providing and fixing porcelain re-wireble fuse carrier and base unit on wooden bound including driving	1	Foot-
	36	Tholes on the board, screws, connections etc. as per specification. (Timboring small or part separately).		Each
		32 amps		

f	all accessories like driver, heat sink made of die cast aluminium with IP 66 protection and 15 KV complete as per specification and P.F. should be greater than 0.9. LED chip efficacy ratio ≥ 120 lumens New tit. 120 watt Supplying and laying following sizes one number FRLS PVC insulated/XLPE, PVC sheathed, steel armoured, aluminium conductors are not provided to the protection of the	1	Each
38	armoured, aluminium conductor power cable of 1.1 KV grade direct in ground at a depth not less than 40 cm and upto 90 cm including excavtion, sand cushioning, protective covering and refilling the trench etc as per specification, IS: 1554 (1988, Part 1) / IS: 7098 (1988, Part 1).	20	mtr
39	Supplying, installation, testing and commissioning of following LED Rope light complete as per specification and IP65, P.F. should be greater than 0.75 9 Watt per Metre White / Warm White	10	mtr

Asstt. Engineer **Municipal Corporation** Bhilai(C.G.)

Sub Engineer Municipal Corporation Bhilai(C.G.)