## MUNICIPAL CORPORATION OF BHILAI

## वार्ड 50 में 2 नग वाटर एटीएम निर्माण कार्य।

(As Per PWD Building SOR 01.01.2015 & NON SOR ITEM)

_	(As Per PWD Building SOR 01.01.2015 8		
5.N.	PARTICULERS OF ITEMS	Quantity	UOM
1	Supply and fixing of precoated galvanized iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-charge) 0.50 mm +/- 5% total coated thickness (TCT). Zinc coating 120gsm as per IS: 277 in 240mpa steel grade. 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches while transportation and should be supplied in single length upto 12 metre on as desired by Engineer-in-charge. The sheet hall be fixed using self-drilling/self-tapping screws of size (5.5x 55mm) with EPDM seal or with polymer coated J or L books, bolts and nuts 8mm diameter with bitumen and G.I. himpet washers or with G.I. himpet washers filled with white lead complete upto any pitch in horizontal/vertical or curved surfaces excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required.	11.52	Sqm
2	Providing and laying nominal mix plain cornert concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work.1:4.8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size).	1.16	Cum
3	Providing and laying ceramic glazed floor tiles conforming to IS: 15622 of approved size, make, colour, shade laid on 20 mm thick. Cement Mortar 1:4 (1 cement: 4 coarse sand) including pointing the joints with white cement mixed with matching pigment etc., complete. Size 300x300mm	11.52	Sqm
4	Providing and fixing M.S. grill of approved pattern made of M.S. flats or square or round bars welded to steel frame of windows etc. including applying a priming coat welded to frame with all necessary fitting complete including applying a priming of red oxide zinc chromate primer.	16.32	Kg
5	Providing and placing on terrace (at all floor levels) polyethylene water storage tank ISI: 12701 marked with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank	3000.00	Litre
6	Providing and laying in trenches G.I. pipes medium class complete with G.I. fittings including excavation of trenches, refilling the same and testing of joints complete:  25 mm dia nominal bore	260.00	Mtr.
7	NON SOR ITEM  Providing and fixing Water Treatment plant based on Reverse Osmosis Technology Design to produce product water at the flow rate of 250,500,1000.  The Proposed water treatment based on RO Technology can even Work continuosly for 10-15½. Hrs. per day.  TREATMENT SCHEME;  A. RAW WATER PUMP  B. MEDIA FILLER UNIT  C. SPECIAL ANTI-SCALENT DOSING SYSTEM  D. MICRON CARTRIDGER FILTER  E. HIGH PRESSURE PUMP  F. R.O. MODULES  G. MEMNRANE CLEANING SYSTEM  H. SV WITH FLUSHING SYSTEM.  I. PROFILE SHEET STRUCTURE FOR RO SYSTEM (SIZE 2.00 x 2.00 Mtr.)  J. Maintenance for 1 Year.  CLIENT TO PROVIDE:  a. Control Supply: 250 Volts (1 Phase, 50 Hz for all Instructios.)  b. Power supply: 440±10 Volts, Three phase 50Hz for high-pressure pump.  c. Labour; As and when required.	2	No.

Executive Engineer

Municiapal Corporation

Bhilai

Assistant Engineer Municipal Corporation Bhilai Sub Engineer Municipal Corporation Bhilai