


# MUNICIPAL CORPORATION BHILAI (C.G.)


## NIT


कार्य का नाम :- वार्ड-18 परदेशी चौक के सामुदायिक भवन में टाइल्स एवं ग्रीलगेट लगाने का कार्य।

Pwd Building Sor 01.01.2015 & Electric Sor 01.06.2020

| S.No. | Description and details of work   | Qty.    | Unit |
|-------|---|---------|------|
| 1     | Providing and laying vitrified floor tiles with double charge/ multi charge printing with water absorption less than 0.5% and conforming to IS : 15622 of approved make in all colours and shades and size mentioned below (+/- 10mm), laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand) including grouting the joints with white cement and matching pigments etc. complete.<br>12.13.1 Size 600x600mm | 66.00   |      |
| 2     | Providing and making 12mm thick cement plaster of mix:  | 37.50   | sqm  |
| 3     | Providing and applying 2mm thick ready mix exterior grade approved make putty (like Birla wall care, Alltek Superfine W/R of (NCL), Asian, ICI, Nerolac, J.K. wall putty) on walls to make the surface smooth and even.   | 135.00  | sqm  |
| 4     | Finishing walls with water proofing cement paint of required shade to give an even shade.<br>14.14.1 On new work (Two or more coats applied @ 3.84 kg/10 sqm)   | 135.00  | sqm  |
| 5     | Distempering with washable distemper manufactured with the cow dung processing to give an even shade.<br>On old work (one or more coats)  | 119.00  | sqm  |
| 6     | Painting on new work (two or more coats) to give an even shade with:<br>14.22.1 Satin synthetic enamel paint  | 135.00  | sqm  |
|       | Premium synthetic enamel paint  | 80.00   | sqm  |
| 7     | Providing and fixing steel door/ window with M.S. sheet 1mm thick, frame of angle iron, diagonal braces of angle/ flat iron of suitable size, 3.00 mm M.S. gusset plates at junctions and corners, all necessary fittings complete including applying a priming coat of red oxide zinc chromate primer.   | 500.00  | kg   |
| 8     | Grading roof for water proofing treatment with:<br>Cement mortar 1:3 (1 cement : 3 coarse sand)   | 3.30    | cum  |
| 10    | Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with matching pigment complete.<br>12.7.1 Size upto 200x300mm   | 45.00   | sqm  |
| 11    | Add 5% for Electrification Work   | 9533.22 | sqm  |

  
Executive Engineer  
Municipal Corporation  
Bhilai (C.G.)

  
Asstt. Engineer  
Municipal Corporation  
Bhilai (C.G.)

  
Sub. Engineer  
Municipal Corporation  
Bhilai (C.G.)