MUNICIPAL CORPORATION OF BHILAI NIT

कार्य का नाम –वार्ड 01 खम्हरिया एस.एल.आर.एम. सेंटर में शेंड संघारण कार्य।

	कार्य का नाम –वार्ड 01 खम्हरिया एस.एल.आर.एम. सटर न	uilding SOR 01.01.2015)	
	(As Per P VVI)	Quantity	UOM
S.N.	PARTICULERS OF ITEMS		
1	Boring, providing and installing cast in situ single under reamed piles of specified diameter and length below pile cap in cement concrete 1:1½:3 (1 cement : 1½ coarse sand : 3 graded and length below pile cap in cement concrete 1:1½:3 (1 cement : 1½ coarse sand : 3 graded and length below pile cap in cement concrete 1:1½:3 (1 cement : 1½ coarse sand : 3 graded and length below pile cap in cement concrete 1:1½:3 (1 cement : 1½ coarse sand : 3 graded and length below pile cap in cement concrete 1:1½:3 (1 cement : 1½ coarse sand : 3 graded and length below pile cap in cement concrete 1:1½:3 (1 cement : 1½ coarse sand : 3 graded and length below pile cap in cement concrete 1:1½:3 (1 cement : 1½ coarse sand : 3 graded and length below pile cap in cement concrete 1:1½:3 (1 cement : 1½ coarse sand : 3 graded and length below pile cap in cement concrete 1:1½:3 (1 cement : 1½ coarse sand : 3 graded and length below pile cap in cement concrete 1:1½:3 (1 cement : 1½ coarse sand : 3 graded and length below pile cap in cement concrete 1:1½:3 (1 cement : 1½ coarse sand : 3 graded and length below pile cap in cement concrete 1:1½:3 (1 cement : 1½ coarse sand : 3 graded and length below pile cap in cement concrete 1:1½:3 (1 cement : 1½ coarse sand : 3 graded and length below pile cap in cement concrete 1:1½:3 (1 cement : 1½ coarse sand : 3 graded and length below pile cap in cement concrete 1:1½:3 (1 cement : 1½ coarse sand : 3 graded and length below pile cap in cement concrete 1:1½:3 (1 cement : 1½ coarse sand : 3 graded and length below pile cap in cement concrete 1:1½:3 (1 cement : 1½ coarse sand : 3 graded and length below pile cap in cement concrete 1:1½:3 (1 cement : 1½ coarse sand : 3 graded and length below pile cap in cement concrete 1:1½:3 (1 cement : 1½ coarse sand : 3 graded and length below pile cap in cement concrete 1:1½:3 (1 cement : 1½ coarse sand : 3 graded and length below pile cap in cap	10.80	Metre
	300 mm dia piles	0.97	Cum
2	concrete mixer in an words up 1.11/2 (1 cement : 11/2 coarse sand : 3 graded stone aggregate 20thin normal		
3	Steel work in tubular (round, square of fectangular by sections, trusses and frame work including cutting, hoisting, fixing in position upto a field sections, trusses and frame work including cutting, hoisting, fixing in position upto a field sections, trusses and frame work including cutting, hoisting, fixing in position upto a field sections, trusses and frame work including cutting, hoisting, fixing in position upto a field sections, trusses and frame work including cutting, hoisting, fixing in position upto a field sections, trusses and frame work including cutting, hoisting, fixing in position upto a field sections, trusses and frame work including cutting, hoisting, fixing in position upto a field sections, trusses and frame work including cutting, hoisting, fixing in position upto a field sections, trusses and frame work including cutting, hoisting, fixing in position upto a field sections, trusses, roof and bottom purlins, base plate, of 5m above plinth level, consisting of columns trusses, roof and bottom purlins, base plate, of 5m above plinth level, consisting of columns trusses, roof and bottom purlins, base plate, of 5m above plinth level, consisting of columns trusses, roof and bottom purlins, base plate, of 5m above plinth level, consisting of columns trusses, roof and bottom purlins, base plate, of 5m above plinth level, consisting of columns trusses, roof and bottom purlins, base plate, of 5m above plinth level, consisting of columns trusses, roof and bottom purlins, base plate, of 5m above plinth level, consisting of columns trusses, roof and bottom purlins, base plate, of 5m above plinth level, consisting of columns trusses, roof and bottom purlins, base plate, of 5m above plinth level, consisting of columns trusses, roof and bottom purlins, base plate, of 5m above plate, and the first level plate, and the	1211.58	Kg
	Supply and fixing of precoated galvanized iron profile sheets (size, shape and pitch of supply and fixing of precoated galvanized iron profile sheets (size, shape and pitch of supply and fixing of precoated galvanized iron profile sheets (size, shape and pitch of supply and fixing of precoated galvanized iron profile sheets (size, shape and pitch of supply and fixing of precoated galvanized iron profile sheets (size, shape and pitch of supply and fixing of precoated galvanized iron profile sheets (size, shape and pitch of supply and fixing of precoated galvanized iron profile sheets (size, shape and pitch of supply and fixing of precoated galvanized iron profile sheets (size, shape and pitch of supply and fixing of precoated galvanized iron profile sheets (size, shape and pitch of supply and fixing of precoated galvanized iron profile sheets).	144.00	Sqm

Executive Engineer Municipal Corporation Bhilai

4

Asstt.Engineer Municipal Corporation Bhilai

corrugation as approved by Engineer-in-charge) 0.50 mm +/-5% total coated thickness (TCT), Zinc coating 120gsm as per IS: 277 in 240mpa steel grade, 5-7.....upto any pitch

and including cutting to size and shape wherever required.

in horizontal/ vertical or curved surfaces excluding the cost of purlins, rafters and trusses

Sub. Engineer **Municipal Corporation** Bhilai