NAGAR PALIK NIGAM BHILAI NIT

मूलभूत सुविधा अंतर्गत वार्ड क्र.—15 अम्बेडकर नगर स्थित सार्वजनिक मंच का संधारण एवं पोताई कार्य। (As per P.W.D BUILDING S.O.R. W.E.F. 01.01.2015 & Electrical S.O.R. 01.06.2020)

S.NO	PARTICULAR	Q	U
1	Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in: Cement Mortar 1:6 (1 cement : 6 coarse sand)		
1		5.60	cum
	Chequered terrazzo tiles 22 mm thick with graded marble chips of size upto 6mm in floors on 25mm thick bed of cement mortar 1:6 (1 cement : 6 coarse sand) jointed with neat cement slurry mixed with pigment to match the shade of tiles including grinding rubbing and polishing complete. Light shade using white cement		
		31.50	sqm
3	15mm thick cement plaster of mix: In Cement Mortar 1:6 (1 cement : 6 fine sand)		
		20.00	sqm
	Providing and applying 2mm thick ready mix exterior grade approved make putty (like Birla wall care, Alltek Superfine W/R of (NCL), Asian, ICI, Nerolac, J.K. wall putty) on walls to make the surface smooth and even.		
		140.00	sqm
	Painting exterior surface with PREMIUM ACRYLIC SMOOTH exterior paint of required shade as per manufacturer's specifications to give protective and decorative finish including cleaning washing of surface etc. complete with: On new work		
		500.00	sqm
	Painting on old work (one or more coats) to give an even shade with: Satin synthetic enamel paint		
		280.00	sqm
I	Structural steel work riveted or bolted or welded in built-up ections, trusses and frames work upto a height of 5m above plinth level, including cutting, hoisting, fixing in position and applying a priming coat of red oxide zinc chromate primer.		•
		150.00	kg

(2)//	
ASSTT.ENGINEER	SUB ENGINEER
Nagar Palik Nigam, Bhilai	Nagar Palik Nigam, Bhilai
	and the state of t