## NAGAR PALIK NIGAM BHILAI

पार्षेद निधि अंतर्गत वार्ड क्र.—19 राजीव नगर निष्ठा मण्डल के समीप सामुदायिक भवन का संधारण एवं नयी सुविधा उपलब्ध कराने का कार्य।

AS PER PWD BUILDING S.O.R 01.01.2015 & Elec. 01.06.2020

ar:	AS PER PWD BUILDING S.O.R 01.01.2015 & Elec. 01.06.2020		
SN	PARTICULAR	QTY	UNIT
1	Providing and laying nominal mix cement concrete with crushed stone aggregate using concrete mixer in foundation, plinth and at ground level excluding cost of form work. 1:4:8 (1 cement : 4		
	coarse sand: 8 graded stone aggregate 40mm nominal size).		
	ourse saind . a graded stone aggregate 40000 novimal sw20).	2.15	cum
2	6 mm thick cement plaster of mix:		
_	In Cement Mortar 1:3 (1 cement : 3 fine sand)		
	in Cement Mortal 1.5 (1 Cement : 5 time saint)	24.74	sqm
3	12mm thick cement plaster of mix:		
,	In Cement Mortar 1:5 (1 cement : 5 fine sand)	-	
	in Centent Mortar 1.5 (1 centent . 5 tine said)	32.48	sqm
-	15 4:1		
4	15mm thick cement plaster of mix:		
	In Cement Mortar 1:6 (1 cement : 6 fine sand)	59.49	sqm
	De la	<del>                                     </del>	
5	Providing and fixing ceramic glazed wall tiles conforming to IS: 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with atching pigment complete. Size above 200x300mm		
	Initiated with deciming pigment completed size doors zoons	89.69	sqm
6	Providing and laying vitrified floor tiles with soluble salt printing, of size 600x600mm with water absorption less than 0.5% and onforming to IS: 15622 of approved make, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand) including grouting the joints with white cement and matching pigments etc. complete.		
-	Indicating prefite the completer	92.44	sqm
7	Providing and applying 2mm thick ready mix exterior grade approved make putty (like Birla wall care, Alltek Superfine W/R of (NCL), Asian, ICI, Nerolac, J.K. wall putty) on walls to make the surface smooth and even.		
		132.02	sqm
8	Distempering with acrylic washable distemper to give an even shade. On new work (Two or more coats)		
	- Couldy	137.25	sqm
	Painting exterior surface with ACRYLIC SMOOTH exterior paint of required shade as per manufacturer's specifications to give protective and decorative finish including cleaning washing of surface etc. complete with: On new work (Two or more coats applied @ 1.43 ltr/ 10 sqm over and including priming coat of exterior primer applied @ 2.20 kg/ 10 sqm)		7. 
ς Λ.	as per putty	40.00	sqm
10	Painting exterior surface with PREMIUM ACRYLIC SMOOTH exterior paint of required shade as per manufacturer's specifications to give protective and decorative finish including cleaning washing of surface etc. complete with: On new work (Two or more coats applied @ 1.43 ltr/ 10 sqm over and including priming coat of exterior primer applied @ 2.20 kg/ 10 sqm)		
-		137.25	sqm
11	Painting on new work (two or more coats) to give an even shade with: Satin synthetic enamel paint		-4.11
		7.24	sqm
12	Premium synthetic enamel paint		- 1-"
	. Terminal symmetre ordanier panie	15.12	sqm
			~4

13	Cement concrete flooring with cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20mm) finished with a floatingcoat of neat cement. 50 mm thick		
1 .7	Providing stainless steel railing/grill made of S.S. flats, hollow S.S. pipe or square/rectangular sections of approved design fixing in stair case, balcony or other places with metal fasteners and stainless steel bolts etc complete. SS Grade 304	44.40	sqm `
	ASSTT.ENGINEER  Nagar Palik Nigam, Bhilai  Nagar Palik Nigam, Bhilai	130.00	kg