MUNICIPAL CORPORATION OF BHILAI

NIT

जोन 04 क्षेत्रांतर्गत नलकूप जल स्त्रोत के समीप सोखपीट संधारण कार्य।

(PWD Building SOR 01.01.2015)

(F WD Building 5			
SN	PARTICULERS OF ITEMS	QTY.	UNIT
1	Excavation for all types and sizes of foundations, trenches and drains or for any other purpose including disposal of excavated stuff upto 1.2 m lift and lead upto 50m (at least 5m away from the excavated area), including dressing and leveling of pits. In all types of soil	145.13	Cum
2	Providing and laying nominal mix plain coment concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work. 1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size).	4.64	Cum
3	Half brick thick honey comb brick work with fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of class designation 4.0 upto plinth levelCement Mortar 1:3 (1 cement : 3 coarse sand)	385.28	Sqm
4	Supplying, filling, spreading & leveling stone boulders/ Gravels/ Coarse sand, in recharge pit, in the required layers and thickness, for all leads & lifts, all complete as per direction of Engineer-in-charge. (excavation of pit will be paid separately). Stone boulders of size range 5 cm to 20 cm, in recharge pit	58.14	Cum
5	Gravels of size range 5 mm to 10 mm, over the existing layer of boulders	29.07	Cum
6	Coarse sand of size range 1.2 mm to 2 mm over existing layer of gravel	21.80	Cum
7	Providing and laying nominal mix reinforced cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work. Extra for precast PCC/ RCC work of any mix including form work, hoisting and fixing in Cement Mortar. 1:2 (1 Cement: 2 coarse sand) and finishing with cement plaster in Cement Mortar 1:3 (1 Cement: 3 coarse sand) but excluding reinforcement.	12.38	Cum
8	Providing and placing in position reinforcement for R.C.C. work including straightening, cutting, bending, binding etc. complete as per drawings including cost of binding wire in foundation and plinth all complete: Thermo-Mechanically treated bars FE 415	743.04	KG
9	Providing and fixing on wall face or under floor UV stabilized Unplasticised Rigid PVC pipes (single socketed) having 3.2mm wall thickness conforming to IS: 13592 (4kg/sqcm) including required couplers, jointing with seal ring conforming to IS: 5382 leaving 10 mm gap for thermal expansion etc complete. 110 mm dia pipe.	215.00	mtr

Executive Engineer
Municiapal Corporation
Bhilai

Assistant Engineer
Municipal Corporation
Bhilai

Sub Engineer

Municipal Corporation

Bhilai