## NAGAR PALIK NIGAM BHILAI

पार्षद निधि अंतर्गत वार्ड क्र.—26 रामनगर मुक्तिधाम क्षेत्रांतर्गत 05 नग नया बोर खन्न कार्य। AS PER P.W.D BUILDING S.O.R (01.01.2015) & ELECTRICAL S.O.R. (01.06.2020)

	AS PER P.W.D BUILDING S.O.R (01.01.2015) & ELECTRICAL S.O.R. (01.0012015)	QTY	UNIT
S.No	. PARTICULARS		
	Boring/drilling bore well perfectly vertical for the specified depth suitable to receive required dia for casing/		
1			1
	strainer pipe, by suitable method prescribed in 18: 2800 (part 1), including contents of all equipments, strata, preparing and submitting strata chart/bore log, including hire & running charges of all equipments, strata, preparing and submitting strata chart/bore log, including hire & running charges of all equipments,	1	- 1
	strata, preparing and submitting strata chart/bore log, including fire & raining the control of Engineer-in-charge upto 90 tools, plants & machineries required for the job, all complete as per direction of Engineer-in-charge upto 90		1
	tools, plants & machineries required for the job, all complete as per direction of any		- 37
	metre depth below ground level. All types of soil	150.00	M
	Boring/drilling bore well perfectly vertical for the specified depth suitable to receive required dia for casing/		
2			
	strainer pipe, by suitable method prescribed in 18: 2800 (part 1), including entering charges of all equipments, strata, preparing and submitting strata chart/bore log, including hire & running charges of all equipments, strata, preparing and submitting strata chart/bore log, including hire & running charges of all equipments,		
	strata, preparing and submitting strata chard-bore log, including line & ramange up to 90 tools, plants & machineries required for the job, all complete as per direction of Engineer—in-charge up to 90 tools, plants & machineries required for the job, all complete as per direction of Engineer—in-charge up to 90 tools, plants & machineries required for the job, all complete as per direction of Engineer—in-charge up to 90 tools, plants & machineries required for the job, all complete as per direction of Engineer—in-charge up to 90 tools, plants & machineries required for the job, all complete as per direction of Engineer—in-charge up to 90 tools, plants & machineries required for the job, all complete as per direction of Engineer—in-charge up to 90 tools, plants & machineries required for the job, all complete as per direction of Engineer—in-charge up to 90 tools, plants & machineries required for the job and plants & machineries r		
	tools, plants & machineries required for the job, all complete as per direction of any		
	metre depth below ground level. Rocky strata including Boulders.	290.00	M
	150 mm dia.		
3	Supplying, assembling, lowering and fixing in vertical position in bore well, ISI marked G.I. casing pipe		
	1 11 TV 1 (I In to data amondments) of reputed & approved make, moraling required		
	charges, fittings & accessories, all complete, for all depths, as per direction of Engineer- in-charge.		
	onargo, mango to arrest and a residence of the control of the cont	120.00	M
	150 mm nominal dia		
1	low at the lowest vivoted or helted or welded in built-up sections, trusses and frames work upto a neighbor.		
-	of 5m-above plinth level, including cutting, hoisting, fixing in position and applying a priming coat of red		
	oxide zinc chromate primer.		1
	For pannel Roy	200.00	kg
	Supplying, installation, testing and commissioning of submersible pump set for water supply system with	ո	
2	submersible motor directly coupled to multi-stage submersible pump of specified discharge capacity, head submersible motor directly coupled to multi-stage submersible pump of specified discharge capacity, head	,	
	delivery size in existing bore well including 2 sets of suitable size holding clamps made out of 50 mm X 6	5	
	mm MS flat, connection with suitable submersible cable of standard length etc. as per specification and IS	:	
	mm MS flat, connection with suitable submersible capie of standard length etc. as per specimental and a summer water Chemical	/	
	694 (2010). Note: submersible Cable should be rust proof, safe from oil / Grease and under water Chemical	Ί	
	abrasion Resistant.	5.00	Each
	1.0 HP, single phase		Lacii
4	Supply, installation, testing and commissioning of 1-3 HP 1 phase submersible motor starter cum contro	1	
	wall/ floor mounted type made out of not less than 1.6 mm thick MS sheet and comprising of following	g	
	panel mounting switchgears there in including connection inter-connection etc. as per specification. a) Phas	e	
	indicating lamps with fuses and toggle switches 1 set b) 1/2/3 HP 1 phase DOL starter with over load and no	0	
	volt relay 1 No c) 25 A "C" curve DPMCB 1 No d) Voltmeter 0-250 V 1 set e) Ammeter 0-10 A 1 set		
		5.00	Each
5	Supplying, laying and fixing following size submersible cable along with GI/PVC/HDFC pipe line or laid i	n	
	ground etc as per specification and IS: 694 (2010). Note: Cable should be rust proof, safe from oil / Greas	se	
	and under water Chemical / abrasion Resistant.		
	and under water Chemical / abrasion Resistant.  3x4.0 sqmm	325.0	0 mtr.
			0 mtr.
5	3x4.0 sqmm	el	0 mtr.
5	3x4.0 sqmm Supplying and laying following sizes one number FRLS PVC insulated/XLPE, PVC sheathed, stearmoured, aluminium conductor power cable of 1.1 KV grade direct in ground at a depth not less than 40 cm	el m	0 mtr.
5	3x4.0 sqmm Supplying and laying following sizes one number FRLS PVC insulated/XLPE, PVC sheathed, stee armoured, aluminium conductor power cable of 1.1 KV grade direct in ground at a depth not less than 40 cannot up to 90 cm including excavtion, sand cushioning, protective covering and refilling the trench etc as power to the same pow	el m	0 mtr.
5	3x4.0 sqmm Supplying and laying following sizes one number FRLS PVC insulated/XLPE, PVC sheathed, stearmoured, aluminium conductor power cable of 1.1 KV grade direct in ground at a depth not less than 40 cannot up to 90 cm including excavtion, sand cushioning, protective covering and refilling the trench etc as perspecification, IS: 1554 (1988, Part 1) / IS: 7098 (1988, Part 1).	el m er	
5	3x4.0 sqmm  Supplying and laying following sizes one number FRLS PVC insulated/XLPE, PVC sheathed, sterarmoured, aluminium conductor power cable of 1.1 KV grade direct in ground at a depth not less than 40 cm and upto 90 cm including excavtion, sand cushioning, protective covering and refilling the trench etc as properly provided in the property of the provided in	el m er 125.0	
5	3x4.0 sqmm  Supplying and laying following sizes one number FRLS PVC insulated/XLPE, PVC sheathed, sterarmoured, aluminium conductor power cable of 1.1 KV grade direct in ground at a depth not less than 40 cand upto 90 cm including excavtion, sand cushioning, protective covering and refilling the trench etc as prespecification, IS: 1554 (1988, Part 1) / IS: 7098 (1988, Part 1).  4 x 10 sq. mm.  Supplying and fixing of following sizes 'B' class G I pipe with all necessary Tee's, bends, sockets in the	el m er 125.0	
7	3x4.0 sqmm  Supplying and laying following sizes one number FRLS PVC insulated/XLPE, PVC sheathed, stee armoured, aluminium conductor power cable of 1.1 KV grade direct in ground at a depth not less than 40 cm and upto 90 cm including excavtion, sand cushioning, protective covering and refilling the trench etc as prespecification, IS: 1554 (1988, Part 1) / IS: 7098 (1988, Part 1).  4 x 10 sq. mm.  Supplying and fixing of following sizes 'B' class G I pipe with all necessary Tee's, bends, sockets in the suction/ delivery line including cutting and threading etc. as per specification.	el m er 125.0	0 mtr
7	3x4.0 sqmm  Supplying and laying following sizes one number FRLS PVC insulated/XLPE, PVC sheathed, sterarmoured, aluminium conductor power cable of 1.1 KV grade direct in ground at a depth not less than 40 cand upto 90 cm including excavtion, sand cushioning, protective covering and refilling the trench etc as prespecification, IS: 1554 (1988, Part 1) / IS: 7098 (1988, Part 1).  4 x 10 sq. mm.  Supplying and fixing of following sizes 'B' class G I pipe with all necessary Tee's, bends, sockets in the	el m er 125.0	0 mtr.

EXECUTIVE ENGINEER Nagar Palik Nigam, Bhilai

SUB ENGINEER

Nagar Palik Nigam, Bhilai