MUNICIPAL CORPORATION OF BHILAI

NIT कार्य का नाम — जोन 01 नेहरू नगर अंतर्गत राशि उद्यान का संधारण कार्य।

As Per PWD Building & Electric SOR 01.01.2015

S.N		Quantity	UOM
1	Demolishing R.C.C. work including stacking of steel bars and disposal of unserviceable material within 50 metre lead.	4.98	cum
2	Providing and fixing form work including centring, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for:2.1.1 Foundations, footings, bases of columns plinth beam, curtain wall in any shape and size and all type of wall below plinth level	33.20	sqm
	Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work.1:1½:3 (1 cement: 1½ coarse sand: 3 graded stone aggregate 20mm nominal size).	4.98	cum
4	Providing and placing in position angle iron post and strut of required size including bottom to be split and bent at right angle in opposite direction for required length and drilling holes upto 10 mm dia as per requirement including priming coat with red oxide zinc chromate primer and placing the post/ strut in cement concrete block.	662.34	kg
111	Structural steel work in single section including cutting, oisting, fixing in position and applying a priming coat of red xide zinc chromate primer.	1196.00	kg
co	roviding and fixing in position chain linked steel wire fabric hade of 4 mm dia G.I. wire of required width in mesh to concrete/ wooden/ angle iron posts including securing and crewing with 2mm dia G.I. wire, G.I. staples, G.I.U-nails or heel pins etc., complete. Aperture 75x75mm	180.00	Sqm

7	Painting exterior surface with PREMIUM ACRYLIC SMOOTH exterior paint of required shade as per manufacturer's specifications to give protective and decorative finish including cleaning washing of surface etc.complete with:On new work (Two or more coats applied @ 1.43 ltr/ 10 sqm over and including priming coat of exterior primer applied @ 2.20 kg/ 10 sqm)	845.00	Sqm
8	Painting exterior surface with PREMIUM ACRYLIC SMOOTH , protective and decorative finish including cleaning washing of surface etc. complete with: On old work (One or more coats applied @ 0.83 ltr/ 10 sqm)	910.00	Sqm
9	Supplying and laying following sizes one number FRLS PVC insulated/XLPE, PVC sheathed, steel armoured, aluminium conductor power cable of 1.1 KV grade direct in ground at a depth not less than 40 cm and upto 90 cm including excavtion, sand cushioning, protective covering and refilling the trench etc as per specification, IS: 1554 (1988, Part 1) / IS: 7098 (1988, Part 1).	256.00	Sqm

८।४ उप अभियंता नगर पालिक निगम भिलाई