


NAGAR PALIK NIGAM BHILAI

NIT

वार्ड क्रं. 16 इंदिरा नगर में छत्तयुक्त मंच एवं शेड का संधारण कार्य।

As Per PWD Building SOR 10.06.2026

SN	PARTICULAR	QTY	UNIT
1	Cement concrete flooring with cement concrete 1:2:4 (1 cement: 2 coarse sand: 4 graded stone aggregate 20mm) finished with a floating coat of neat cement. 50 mm thick		
		93.75	sqm
2	Neat Cement punning.		
		93.75	sqm
3	Providing & laying 60mm thick precast interlocking concrete blocks of approved size (approx 305 sqcm) and shape/ pattern, over 40 mm thick kg/sq.cm Plain/normal coloured precast interlock concrete block		
		60.00	sqm
4	Chequerred precast cement concrete tiles 22mm thick in footpath & courtyard jointed with neat cement slurry mixed with pigment to match the shade of tile including cleaning of joint etc complete on 20 mm thick bed of cement mortar 1:4 (1 cement:4 coarse sand): Light shade using white cement		
		24.00	sqm
5	Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work. 1:1½:3 (1 cement: 1½ coarse sand: 3 graded stone aggregate 20mm nominal size).		
		0.76	cum
6	Extra for necessary grinding and polishing to get mirror finish on KOTA/ Marble Stone flooring/ steps/treads instead of normal grinding and polishing.		
		129.50	sqm
7	Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in: Cement Mortar 1:6 (1 cement: 6 coarse sand)		
		17.10	cum
8	Providing and making 12mm thick cement plaster of mix: In Cement Mortar 1:6 (1 cement: 6 fine sand)		
		56.25	sqm
9	Providing and applying plaster of paris putty over plastered wall surface including scaffolding complete More than 2 mm thickness to make surface even and smooth in true plumb and line and level.		
		133.28	sqm
10	Distempering with acrylic washable distemper to give an even shade. On new work (Two or more coats)		
		145.20	sqm

11	White washing/ Colour washing with lime to give an even shade in Three or more Coats for New surface as per relevant IS code 6278:1971 Consumption of lime 3.50kg/10 Sqm with all tools tackles and labour etc.		
		285.00	sqm
12	Providing and applying plaster of paris putty over plastered wall surface including scaffolding complete Upto 2 mm thickness to make surface even and smooth in line and level.		
		285.00	sqm
 ASSTT.ENGINEER Nagar Palik Nigam, Bhilai  SUB ENGINEER Nagar Palik Nigam, Bhilai			